Hamilton

## making connections beautifully

	Wiring Accessories •	Smart Lighting Control • Wireless Audio				
7BC4XTEBL						
Hartland CFX Colours Jet Black 4x250W/210VA Resistive/Inductive Trailing Edge Push On/Off Rotary Multi-Way Dimmers Black						
Item Image	Wiring Dimensions					
	Multi-Way Wiring using Retractive PTM Rocker Switches	ESDOCOOLOURS ATTENDE CE COLOURS ATTENDE CE COLOURS MUITI-Way Dimmer				
Primary Range	Hartland CFX Colours					
Insert Type	4 gang 250W/210VA Resistive/Inductive Trailing Edge Push On/Off Rotary Multi-Way Dimmer					
Plate Finish	Hartland CFX Colours Jet Black					
Insert Colour	Black					
EAN13 Barcode	5017504006808					
Commodity Code	85365015					
Luckins TSI	394187325					
ETIM Class	EC000025					
Dimensions (Nominal)	Double: Height = 86.0mm Width = 146.0mm Depth = 5.0mm					
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Push					
Minimum Wall Box Depth	35mm					
Wattage	250W Resistive 210VA Inductive					
Switched Poles	Single					
Current Rating	1.1 Amps per gang					
Voltage	220/250V AC					
Maximum Load	250W Resistive per gang 210VA Inductive Min Load 25W/25VA					
Mains Frequency	50Hz					
IP Rating	IP2XD					
Contact Gap Minimum	None					
Terminal Capacity 1	2x1mm <sup>2</sup>					
Terminal Capacity 2	2x1.5mm <sup>2</sup>					
Earth Terminal Capacity 1	5x1mm <sup>2</sup>					
Earth Terminal Capacity 2	4 x 1.5mm2					
Earth Terminal Capacity 3	3 x 2.5mm2					
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand					
Earth Terminal Capacity 5	1 x 6mm2					
Product Class 1	Face plate must be earthed					
Ambient Operating Temperature	-5° to +40°C					
Recommended Location	Internal Use Only					
Maximum Installation Altitude	2000m					
Standard/Approval Additional Notes	BS EN 60669-2-1 TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product)					

SL

# Hamilton

#### making connections beautifully

CERT. No. FM11238

Wiring Accessories • Smart Lighting Control • Wireless Audio

#### 7BC4XTEBL

### Hartland CFX Colours Jet Black 4x250W/210VA Resistive/Inductive Trailing Edge Push On/Off Rotary Multi-Way Dimmers Black

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we canno guarantee an exact colour match and shading of certain finishes.		Correct as at 05 July 2022 09:18 AM E&OE		
	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84		Listed in Trimble	riba product selector	

SL