




7BC6126B

Hartland CFX Colours Jet Black 1 gang 10/16A 220/250V AC German Unswitched Socket Black

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  <p>Note: This socket is Non Polarised</p> |  <p>Hamilton® HARTLAND CFX COLOURS 6126 Unswitched German Socket</p> |
| Primary Range | Hartland CFX Colours | |
| Insert Type | 1 gang 10/16A 220/250V AC German Unswitched Socket | |
| Plate Finish | Hartland CFX Colours Jet Black | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504006839 | |
| Commodity Code | 85363010 | |
| Luckins TSI | 394187370 | |
| ETIM Class | EC000125 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Push | |
| Minimum Wall Box Depth | 47mm | |
| Switched Poles | None | |
| Current Rating | 10/16 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 16 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 3x2.5mm² | |
| Terminal Capacity 2 | 3x4mm² | |
| Terminal Capacity 3 | 2x6mm² Multi-strand | |
| Terminal Capacity 4 | 1x10mm² | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN ISO 5733 + IEC 60884-1 | |
| Additional Notes | Shuttered: Yes | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 09:18 AM E&OE |