





## 7BCJ12B

### Hartland CFX Colours Jet Black 1 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																					
	<p>Datcom Module Rear View RJ11 / 12 Socket Rear View</p>  <p>Cable tie anchor</p> <p>View of Transparent Cover</p>  <p>8 Pin RJ11 / 12 Wiring Colour Codes:</p> <table border="1"> <tr> <td>1</td> <td>GREEN</td> <td>BLUE</td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>GREEN</td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>RED</td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>BLACK</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> <td>WHITE</td> </tr> <tr> <td>7</td> <td>NOT USED</td> <td>NOT USED</td> </tr> </table> <p>Main Wire Colour shown in CAPITALS</p>	1	GREEN	BLUE	2	ORANGE / White	YELLOW	3	WHITE / Blue	GREEN	4	BLUE / White	RED	5	WHITE / Orange	BLACK	6	WHITE / Green	WHITE	7	NOT USED	NOT USED	<p>Hamilton® HARTLAND CFX COLOURS</p> <p>J12 1 gang RJ12 Outlet Unshielded 6 wire</p> 
1	GREEN	BLUE																					
2	ORANGE / White	YELLOW																					
3	WHITE / Blue	GREEN																					
4	BLUE / White	RED																					
5	WHITE / Orange	BLACK																					
6	WHITE / Green	WHITE																					
7	NOT USED	NOT USED																					
Primary Range	Hartland CFX Colours																						
Insert Type	1 gang RJ12 Outlet - Unshielded																						
Plate Finish	Hartland CFX Colours Jet Black																						
Insert Colour	Black																						
EAN13 Barcode	5017504006969																						
Commodity Code	85176990																						
Luckins TSI	394187639																						
ETIM Class	EC001264																						
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm																						
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push																						
Minimum Wall Box Depth	35mm																						
Switched Poles	N/A																						
Current Rating	n/a																						
IP Rating	IP2XD																						
Contact Gap Minimum	N/A																						
Earth Terminal Capacity 1	5x1mm <sup>2</sup>																						
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>																						
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>																						
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand																						
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>																						
Product Class 1	Must be earthed (ref BS7671 415.2.1)																						
Ambient Operating Temperature	-5° to +40°C																						
Recommended Location	Internal Use Only																						
Maximum Installation Altitude	2000m																						
Standard/Approval	N/A																						
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																						
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667																						
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																					
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 09:18 AM E&OE																					

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM1238