

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7BCSS2BL-B

Hartland CFX Colours Jet Black 2 gang 13A Double Pole Switched Socket Black/Black

Harriand CFX Colours	Item Image	Wiring	Dimensions	
Pater Tippe			SS2 Switched Socket	
Pater Tippe	Primary Range	Hartland CFX Colours		
Plate Finish				
Insert Colour				
EAN13 Barcode 5017504007140 Commodity Code 85363010 Luckins TSI 394187723 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Width = 146.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 120.6mm Gnd Fixing = CFX Push Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Walls Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4x2.5mm² Terminal Capacity 1 4x2.5mm² Terminal Capacity 3 2x6mm² Multi-Strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 5 2x6mm² Multi-Strand Earth Terminal Capacity 6 1x10mm² Earth Terminal Capacity 6 1x10mm² Earth Terminal Capacity 7 1x10mm² Earth Terminal Capacity 8 2x6mm² Multi-Strand Earth Terminal Capacity 9 1x10mm² Earth Termin				
Commodity Code         85363010           Luckins TSI         394187723           ETIM Class         EC000125           Dimensions (Nominal)         Double: Height = 86.0mm Width = 146.0mm Depth = 5.0mm           Weight         150 GR           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Push           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²				
Luckins TSI         394187723           ETIM Class         EC000125           Dimensions (Nominal)         Double: Height = 86.0mm Width = 146.0mm Depth = 5.0mm           Weight         150 GR           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Push           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6m				
ETIM Class				
Dimensions (Nominal)   Double: Height = 86.0mm   Width = 146.0mm   Depth = 5.0mm				
Weight				
Fixing Hole Centres         Box Fixing = 120.6mm         Grid Fixing = CFX Push           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2				
Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2				
Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2				
Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2		Double		
Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Current Rating	13 Amp		
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Voltage	220/250V AC		
IP Rating	Maximum Load	13 Amp		
Contact Gap Minimum  Terminal Capacity 1  4x2.5mm²  Terminal Capacity 2  3x4mm²  Terminal Capacity 3  2x6mm² Multi-Strand  Terminal Capacity 4  1x10mm²  Earth Terminal Capacity 1  4x2.5mm²  Earth Terminal Capacity 1  Earth Terminal Capacity 2  3x4mm²  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  1x10mm²  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval	Mains Frequency	50Hz		
Terminal Capacity 1 4x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-Strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	IP Rating	IP2XD		
Terminal Capacity 2 3x4mm²  Terminal Capacity 3 2x6mm² Multi-Strand  Terminal Capacity 4 1x10mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 3 1x10mm²  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Contact Gap Minimum	3mm		
Terminal Capacity 2 3x4mm²  Terminal Capacity 3 2x6mm² Multi-Strand  Terminal Capacity 4 1x10mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 3 1x10mm²  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Terminal Capacity 1	4x2.5mm²		
Terminal Capacity 4	Terminal Capacity 2	3x4mm²		
Terminal Capacity 4	Terminal Capacity 3	2x6mm² Multi-Strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 1363-2		1x10mm²		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  1x10mm²  Product Class 1  Must be earthed  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  8S 1363-2	Earth Terminal Capacity 1	4x2.5mm²		
Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 2	3x4mm²		
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 3	2x6mm² Multi-Strand		
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 4	1x10mm²		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS 1363-2	Product Class 1	Must be earthed		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS 1363-2	Ambient Operating Temperature	-5° to +40°C		
Maximum Installation Altitude2000mStandard/ApprovalBS 1363-2		Internal Use Only		
· · ·	Maximum Installation Altitude	2000m		
	Standard/Approval	BS 1363-2		
		Dual Earth: Yes		



SL

# making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7BCSS2BL-B

Hartland CFX Colours Jet Black 2 gang 13A Double Pole Switched Socket Black/Black				
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes	Correct as at 05 July 2022 09:18 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









