





7RC2J45W

Hartland CFX Colours Pillar Box Red 2 gang RJ45 CAT 5E Outlet - Unshielded White

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |   <p>Please always check with the colour coding found on the product.</p> |  |

| | | |
|---|---|---|
| Primary Range | Hartland CFX Colours | |
| Insert Type | 2 gang RJ45 CAT 5E Outlet - Unshielded | |
| Plate Finish | Hartland CFX Colours Pillar Box Red | |
| Insert Colour | White | |
| EAN13 Barcode | 5017504007355 | |
| Commodity Code | 85176990 | |
| Luckins TSI | 394188683 | |
| ETIM Class | EC001264 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Weight | 110 GR | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Push | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| Current Rating | n/a | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5x1mm ² | |
| Earth Terminal Capacity 2 | 4x1.5mm ² | |
| Earth Terminal Capacity 3 | 3x2.5mm ² | |
| Earth Terminal Capacity 4 | 1 x 4mm ² Multi-Strand | |
| Earth Terminal Capacity 5 | 1x6mm ² | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | N/A | |
| EuroFix Additional Notes | Can be used in both EIA 568A and EIA 568B wiring schedules | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 09:18 AM E&OE |