

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7RC2XLEDITB100BL

Hartland CFX Colours Pillar Box Red 2g 100W LED 2 Way Push On/Off Rotary Dimmer Black

Dimensions Item Image Wiring Hamilton Hartland CFX COLOURS 2XLEDITB LEDITB100 2 Way Dimmer Hartland CFX Colours Primary Range 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Insert Type Plate Finish Hartland CFX Colours Pillar Box Red Insert Colour EAN13 Barcode 5017504080204 Commodity Code 85365015 Luckins TSI 403364233 ETIM Class EC000025 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Push Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single **Current Rating** 0.3A Per Gang Voltage 230V AC Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 _ 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed **Ambient Operating Temperature** -5°C to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks CFX is a Registered Trade Mark No 2398667 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is as part of our development programme.

Therefore, we reserve the right to alter designs BS EN ISO 9001: 2015 Quality Management System. correct at the time of going to press and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 05 July 2022 09:18 AM Illustrations and diagrams are reproduced within the limitations of reproduction and printing

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com www.hamilton-litestat.com www.hamilton.

process and are not binding.









