

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio


## **7RCDENTB**

Hartland CFX Colours Pillar Box Red Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible) Black

## SAT1 SAT2

Item Image

## Wiring



EMC gasket which is located on the cover.

3. Insert the conductor into the terminal slot which is located in the casing of the module.

4. Before closing the cover check to ensure that conductor, screening braid and cable are in the correct position as shown below.



## Dimensions



And the second s	DOC Dambal AN HAVE PM	
	omth omin.	
Primary Range	Hartland CFX Colours	
Insert Type	Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out (DAB Compatible)	
Plate Finish	Hartland CFX Colours Pillar Box Red	
Insert Colour	Black	
EAN13 Barcode	5017504007645	
Commodity Code	85367000	
Luckins TSI	394188230	
ETIM Class	EC000439	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Push	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
Current Rating	n/a	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm <sup>2</sup>	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 50581:2012, BS EN 60728-4:2008, BS EN 50083-2: 2012/A1:2015	
EuroFix Additional Notes	Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible)	
Frequencies 1	TV=5-68 MHz 125-860 MHz	
Frequencies 2	FM=88-108 MHz	
Frequencies 3	SAT DC=950-2200 MHz	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84

Illustrations and diagrams are reproduced within the limitations of reproduction and printing







and dimensions without prior notice.





Correct as at 05 July 2022 09:19 AM E&OE

