

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio


## 7RCSS1USBBL-B

Hartland CFX Colours Pillar Box Red 1 gang 13A Single Pole Switched Socket with 1 USB Outlets 1x2.1A Black/Black


## Item Image



## Wiring



## Dimensions



| Primary Range   | Hartland CFX Colours  |   |
|---|---|---|
| Insert Type   | 1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A                                       |   |
| Plate Finish  | Hartland CFX Colours Pillar Box Red   |   |
| Insert Colour   | Black/Black   |   |
| EAN13 Barcode   | 5017504089269   |   |
| Commodity Code  | 85363010  |   |
| Luckins TSI   | 404388357   |   |
| ETIM Class  | EC000125  |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Push  |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Switched Poles  | Single  |   |
| Current Rating  | 13 Amp, USB 1 x 2.1A  |   |
| Voltage   | 180/250V AC, USB = 5V   |   |
| Maximum Load  | 13 Amp, USB = 2.1A  |   |
| Mains Frequency   | 50/60Hz   |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 3x2.5mm²  |   |
| Terminal Capacity 2   | 3x4mm²  |   |
| Terminal Capacity 3   | 2x6mm² Multi-Strand   |   |
| Earth Terminal Capacity 1   | 3x2.5mm²  |   |
| Earth Terminal Capacity 2   | 3x4mm²  |   |
| Earth Terminal Capacity 3   | 2x6mm² Multi-Strand   |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -15°C to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS 1363 + BS 5733 + EN 60950-1  |   |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667   |   |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.











Correct as at 05 July 2022 09:19 AM E&OE