



## 79C1XLEDITB100

Hartland CFX Antique Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

Item Image	Wiring	Dimensions
		 <p>Hamilton® HARTLAND CFX 1XLEDITB LEDITB100 2 Way Dimmer</p>
Primary Range	Hartland CFX	
Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer	
Plate Finish	Hartland CFX Antique Brass	
Insert Colour	Antique Brass	
EAN13 Barcode	5017504079680	
Commodity Code	85365015	
Luckins TSI	403372607	
ETIM Class	EC000025	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Weight	200 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Wattage	5-100W (10 LED Lamps MAX)	
Switched Poles	Single	
Current Rating	0.4A	
Voltage	230V AC	
Maximum Load	5-100W (10 LED Lamps MAX)	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Terminal Capacity 1	2X1mm²	
Terminal Capacity 2	2x1.5mm²	
Earth Terminal Capacity 1	5x1mm²	
Earth Terminal Capacity 2	4X1.5mm²	
Earth Terminal Capacity 3	3X2.5mm²	
Earth Terminal Capacity 4	1X4mm² Multi-Strand	
Earth Terminal Capacity 5	1X6mm²	
Product Class 1	Face plate must be earthed	
Ambient Operating Temperature	-5°C to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-2-1	
Additional Notes	Trailing Edge & Leading Edge Dimmer	

## 79C1XLEDITB100

### Hartland CFX Antique Brass 1g 100W LED 2 Way Push On/Off Rotary Dimmer Antique Brass

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:56 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in  
**LUCKINS**



CERT. No. FM11238