


## 77CTCMB

### Hartland CFX Bright Chrome 1 gang Telephone Master Black

Item Image	Wiring	Dimensions
	<div><div><div>Pin No.</div><div>1</div><div>2</div><div>3</div><div>4</div><div>5</div><div>6</div></div><div><div>BT Wiring Schedule Colour Codes:</div><div>Striped Wires</div><div>GREEN / White</div><div>BLUE / White</div><div>ORANGE / White</div><div>WHITE / Orange</div><div>WHITE / Blue</div><div>WHITE / Green</div></div><div><div>Main Wire Colour shown in CAPITALS</div></div></div> <p>Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p>The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	<div><div><div><div><div>Hamilton®</div><div>HARTLAND CFX</div><div>TCM</div><div>Telephone Master Socket</div></div></div><div><div><div>86.0</div><div>86.0</div><div>5.0</div><div>15.0</div></div></div></div></div>
Primary Range	Hartland CFX	
Insert Type	1 gang Telephone Master	
Plate Finish	Hartland CFX Bright Chrome	
Insert Colour	Black	
EAN13 Barcode	5017504271640	
Commodity Code	85176990	
Luckins TSI	388240430	
ETIM Class	EC000018	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	N/A	
Current Rating	n/a	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm²	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 6312:2:2	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:54 AM E&OE