

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 77CTCSB

Hartland CFX Bright Chrome 1 gang Telephone Slave Black

# Item Image




# Wiring

# Wiring Schedule Colour Codes: Striped Wires GREEN / White BLUE / White ORANGE / White WHITE / Orange WHITE / Blue WHITE / Green Vire Colour shown in CAPITALS

Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.

The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may

## **Dimensions**



	be connected. All sockets are connected in parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above.	
Primary Range	Hartland CFX	
Insert Type	1 gang Telephone Slave	
Plate Finish	Hartland CFX Bright Chrome	
Insert Colour	Black	
EAN13 Barcode	5017504271657	
Commodity Code	85176990	
Luckins TSI	388240456	
ETIM Class	EC000018	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	N/A	
Current Rating	n/a	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm²	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 6312:2:2	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes	Correct as at 05 July 2022 08:54 AM E&OE

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84













process and are not binding.