Hamilton

## making connections beautifully

| Wiring Accessories • Smart Lighting Control • Wireless Audio   |   |  |
|--|---|--|
|  | 77CTVFMW  |  |
| Hartland C   |   | n/2 out M/bito   |
|  | FX Bright Chrome Isolated TV/FM Diplexer 1in  |  |
| Item Image   | Wiring  | Dimensions   |
|  | Screen<br>Under Cable   | HERTLAND CFX<br>TVFM<br>Isolated TV/FM Diplexer 1in/2out   |
| Primary Range  | Hartland CFX  |  |
| Insert Type  | Isolated TV/FM Diplexer 1in/2out  |  |
| Plate Finish   | Hartland CFX Bright Chrome  |  |
| Insert Colour  | White   |  |
| EAN13 Barcode  | 5017504270636   |  |
| Commodity Code   | 85367000  |  |
| Luckins TSI  | 388240511   |  |
| ETIM Class   | EC000439  |  |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips   |  |
| Minimum Wall Box Depth   | 25mm  |  |
| Switched Poles   | N/A   |  |
| Current Rating   | n/a   |  |
| IP Rating  | IP2XD   |  |
| Contact Gap Minimum  | N/A   |  |
| Earth Terminal Capacity 1  | 5x1mm <sup>2</sup>  |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5  | 1 x 6mm2  |  |
| Product Class 1  | Must be earthed (ref BS7671 415.2.1)  |  |
| Ambient Operating Temperature  | -5° to +40°C  |  |
| Recommended Location   | Internal Use Only   |  |
| Maximum Installation Altitude  | 2000m   |  |
| Standard/Approval  | BS 5733   |  |
| Patents and Trademarks   | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445                   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.                              | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.   | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.                                   | Correct as at 05 July 2022 08:55 A<br>E&C  |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville<br>T: +44 (0)1747 860088 Registered<br>E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Road, Brislington, Bristol, BS4 5NZ<br>Office 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimbe product PLSPUs LUCKINS  |

SL