

7BGCSHSQG

Hartland CFX Basalt Gray Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Quartz Grey

| Item Image | Wiring | Dimensions |
|-------------------------------|--|------------|
| | | |
| Primary Range | Hartland CFX | |
| Insert Type | Shaver Dual Voltage Unswitched Socket (Vertically Mounted) | |
| Plate Finish | Hartland CFX Vertical Basalt Gray | |
| Insert Colour | Quartz Grey | |
| EAN13 Barcode | 5017504093426 | |
| Commodity Code | 85363010 | |
| ETIM Class | EC000186 | |
| Dimensions (Nominal) | Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm | |
| Weight | 905 GR | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 47mm | |
| Switched Poles | None | |
| Current Rating | 20VA | |
| Voltage | 220/250V AC | |
| Maximum Load | 200/250V input; 115/230V 20VA output | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 5 x1mm ² | |
| Terminal Capacity 2 | 4x1.5mm ² | |
| Terminal Capacity 3 | 3x2.5mm ² | |
| Terminal Capacity 4 | 2x4mm ² Multi-strand | |
| Terminal Capacity 5 | 1x6mm ² | |
| Earth Terminal Capacity 1 | 9x1mm ² | |
| Earth Terminal Capacity 2 | 6x1.5mm ² | |
| Earth Terminal Capacity 3 | 4x2.5mm ² | |
| Earth Terminal Capacity 4 | 2x4mm ² Multi-strand | |
| Earth Terminal Capacity 5 | 1x6mm ² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 61558-2-5 + BS 4573 | |
| Additional Notes | Must be mounted vertically. Shuttered :Yes. Box Depth 47mm | |

7BGCSHSQG

Hartland CFX Basalt Gray Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Quartz Grey

| | | |
|---|---|---|
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 08:57 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble**
LUCKINS



CERT. No. FM11238