

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7BGCT23

Hartland CFX Basalt Gray 3 gang 20AX 2 Way Toggle Basalt Gray

Item Image	Wiring	Dimensions
		Hemilton HARTLAND CFX T23 2 Way Toggle
	Aberrative 2 very sentring Long In Long Out Intermediate sentring	145.0
Primary Range	Hartland CFX	
Insert Type	3 gang 20AX 2 Way Toggle	
Plate Finish	Hartland CFX Basalt Gray	
Insert Colour	Basalt Gray	
EAN13 Barcode	5017504093518	
Commodity Code	85363030	
ETIM Class	EC001590	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0	mm
Veight	380 GR	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	20AX	
/oltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
P Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5x1mm²	
Terminal Capacity 2	4x1.5mm²	
Ferminal Capacity 3	2x2.5mm²	
Ferminal Capacity 4	2x4mm² Multi-strand	
Ferminal Capacity 5	1x6mm²	
Earth Terminal Capacity 1	6x1mm²	
Earth Terminal Capacity 2	5x1.5mm²	
Earth Terminal Capacity 3	3x2.5mm²	
arth Terminal Capacity 4	2x4mm² Multi-strand	
arth Terminal Capacity 5	1x6mm²	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7BGCT23

Hartland CFX Basalt Gray 3 gang 20AX 2 Way Toggle Basalt Gray			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 05 July 2022 08:57 AM	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









