Hamilton

making connections beautifully

	Wiring Accessories •	Smart Lighting Control • Wireless Audio
	<u>78C2J45B</u>	
Hartland CEX	Black Nickel 2 gang RJ45 CAT 5E Outlet - U	nshielded Black
Item Image	Wiring	Dimensions
	RJ45 CAT5e Rew View RJ45 CAT5e Rew View Colour Codes RJ45 CAT5e and CAT5 Wring Colour Codes RJ45 CAT5e and CAT5 Wring RJ45 CAT5e Wring RJ45 CAT5e and CAT5 Wrin	HEILOFA 245 2 gang RJ45 - CAT 5E Outlet Unshielded 8 wire
Primary Range	Cable tie anchor Hartland CFX	
Insert Type	2 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Hartland CFX Black Nickel	
nsert Colour	Black	
EAN13 Barcode	5017504281588	
Commodity Code	85176990	
uckins TSI	388241196	
TIM Class	EC001264	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Veight	110 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
/inimum Wall Box Depth	35mm	
Switched Poles	N/A	
Current Rating	n/a	
P Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm ²	
arth Terminal Capacity 2	4x1.5mm ²	
arth Terminal Capacity 3	4x1.5mm ²	
arth Terminal Capacity 4	1 x 4mm ² Multi-Strand	
arth Terminal Capacity 5	1 x 4mm² Mulu-Strand	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Induct Class 1	-5° to +40°C	
Recommended Location	Internal Use Only	
Aaximum Installation Altitude	2000m	
Standard/Approval	N/A	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:55 E8
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville 1: +44 (0)1747 860088 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble product selector Disspite Certing Product

SL