Hamilton

making connections beautifully

| Wiring Accessories • Smart Lighting Control • Wireless Audio | | |
|--|---|--|
| <u>78C45NB</u> | | |
| Hartland CFX Black Nickel 1 gang 45A Double Pole Rocker and Neon Red/Black | | |
| | | |
| Item Image | Wiring | Dimensions |
| | L FEED N | HEIDILOOD HARTLAND CFX 45N Double Pole Red Rocker & Neon |
| | | |
| Primary Range | Hartland CFX | |
| Insert Type | 1 gang 45A Double Pole Red Rocker + Neon | |
| Plate Finish | Hartland CFX Black Nickel | |
| Insert Colour | Red/Black | |
| EAN13 Barcode | 5017504281717 | |
| Commodity Code | 85363030 | |
| | 388240621 | |
| ETIM Class | EC001590 Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Dimensions (Nominal) | | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips 35mm | |
| Minimum Wall Box Depth | | |
| Switched Poles | Double 45 Amp | |
| Current Rating Voltage | 45 Amp 220/250V AC | |
| Maximum Load | 45 Amp | |
| Maximum Load Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3x6mm ² | |
| Terminal Capacity 2 | 2x10mm ² | |
| Terminal Capacity 3 | 1x16mm ² | |
| Earth Terminal Capacity 1 | 3x6mm ² | |
| Earth Terminal Capacity 2 | 2x10mm ² | |
| Earth Terminal Capacity 3 | 1x16mm ² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 08:55 AM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com wwww.hamilton-litestat.com wwww.hamilton-litestat.com www.hamilton-li | | |