Hamilton

## making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio 78CDTVMB Hartland CFX Black Nickel 1 gang Non-Isolated TV (Male) (DAB Compatible) Black					
			Item Image	Wiring	Dimensions
	EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable	HARTLAND CFX DTVM Non-Isolated TV (male)			
Primary Range	Hartland CFX				
Insert Type	1 gang Non-Isolated TV (Male) (DAB Compatible)				
Plate Finish	Hartland CFX Black Nickel				
Insert Colour	Black				
EAN13 Barcode	5017504281519				
Commodity Code	85367000				
	388240744				
ETIM Class	EC00439				
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth	35mm				
Switched Poles	N/A				
Current Rating	n/a				
IP Rating	IP2XD				
Contact Gap Minimum	N/A				
Earth Terminal Capacity 1	5x1mm <sup>2</sup>				
	4 x 1.5mm2				
Earth Terminal Capacity 2	3 x 2.5mm2				
Earth Terminal Capacity 3	1 x 4mm2 Multi-strand				
Earth Terminal Capacity 4 Earth Terminal Capacity 5					
	1 x 6mm2 Must be earthed (ref BS7671 415.2.1)				
Product Class 1	-5° to +40°C				
Ambient Operating Temperature	Internal Use Only				
Recommended Location					
Maximum Installation Altitude	2000m				
Standard/Approval	BS 5733. BS EN 50083-2: 2012/A1:2015. BS EN 61169-2:2007 TV Outlet (IEC 169-2 male socket) Usually used for FM (DAB) outlet				
EuroFix Additional Notes	FM DC=5-2200 MHz				
Frequencies 1 Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:55 AM E&OE			
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Re T: +44 (0)1747 860088 Registered O E: info@hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble product selector InSSPius (ER No. FAIl128			

SL