

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

78CT22

Hartland CFX Black Nickel 2 gang 20AX 2 Way Toggle Black Nickel

Transand CFA Black Nicker 2 gang 20AA 2 way Toggle Black Nicker					
Item Image	Wiring	Dimensions			
	Alternative 2 way westering	Hemilton HARTLAND CFX T22 2 Way Toggle			
Primary Range	Hartland CFX				
Insert Type	2 gang 20AX 2 Way Toggle				
Plate Finish	Hartland CFX Black Nickel				
Insert Colour	Black Nickel				
EAN13 Barcode	5017504289263				
Commodity Code	85363030				
Luckins TSI	388241219				
ETIM Class	EC001590				
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm				
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips				
Minimum Wall Box Depth Switched Poles	35mm				
	Single				
Current Rating Voltage	20AX 220/250V AC				
Maximum Load	20 Amp inductive				
Mains Frequency	20 Amp inductive 50Hz				
IP Rating	IP2XD				
Contact Gap Minimum	3mm				
Terminal Capacity 1	5x1mm²				
Terminal Capacity 2	4x1.5mm²				
Terminal Capacity 3	2x2.5mm²				
Terminal Capacity 4	2x4mm² Multi-strand				
Terminal Capacity 5	1x6mm²				
Earth Terminal Capacity 1	6x1mm²				
Earth Terminal Capacity 2	5x1.5mm²				
Earth Terminal Capacity 3	3x2.5mm²				
Earth Terminal Capacity 4	2x4mm² Multi-strand				
Earth Terminal Capacity 5	1x6mm²				
Product Class 1	Must be earthed				
Ambient Operating Temperature	-5° to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-1				



making connections beautifully

vviring Accessories	 Smart Lighting 	Control •	vvireless Aud	וב
---------------------	------------------------------------	-----------	---------------	----

78CT22

Hartland CFX Black Nickel 2 gang 20AX 2 Way Toggle Black Nickel				
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:56 AM E&OE		

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









