Hamilton

making connections beautifully

| Wiring Accessories • Smart Lighting Control • Wireless Audio | | |
|---|--|--|
| | 78CTCMB | |
| Hartla | Ind CFX Black Nickel 1 gang Telephone Maste | ar Black |
| lialua | | |
| Item Image | Wiring | Dimensions |
| | Pin BT Wiring Schedule Colour Codes: Striped Wires 1 GREEN / White 2 BLUE / White 3 ORANGE / White 4 WHITE / Orange 5 WHITE / Blue Main Wire Colour shown in CAPITALS Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected. The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected to parallel. ie Pin 1 to Pin 1; Pin 2 to Pin 2; etc. as shown in the diagram above. | HEIRILAND CFX TCM Telephone Master Socket |
| Primary Range | Hartland CFX | |
| Insert Type | 1 gang Telephone Master | |
| Plate Finish | Hartland CFX Black Nickel | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504281656 | |
| Commodity Code | 85176990 | |
| Luckins TSI | 388241345 | |
| ETIM Class | EC000018 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | N/A | |
| Current Rating | n/a | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5x1mm ² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 6312:2:2 | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 08:56 A E&O |
| | Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimbe LUCKINS Rector Display Cat. No. 1411228 |