



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

78CW10DPBK-B

Primary Range	Hartland CFX Black Nickel Wide Rocker 1 gang 10AX Double Pole Black Nickel/Black			
Primary Range				
Primary Range				
Insert Type				
Plate Finish				
Insert Colour	Wide Rocker - 1 gang 10AX Double Pole Rocker			
EAN13 Barcode 5051164009717 Commodity Code 85363010 Luckins TSI 453341097 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm²				
Commodity Code 85363010 Luckins TSI 453341097 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	Black Nickel/Black			
Luckins TSI 453341097 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	5051164009717			
ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 4x1.5mm² Earth Terminal Capacity 5 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	85363010			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	453341097			
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	EC001590			
Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Earth Terminal Capacity 5 Ix6mm²				
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand	25mm			
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	Double			
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm²				
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²	220/250V AC			
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Contact Gap Minimum Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm²				
Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Terminal Capacity 3				
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm²				
Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm²				
Earth Terminal Capacity 5 1x6mm ²				
Product Class 1 Must be earthed				
	-5° to +40°C			
	Internal Use Only			
	2000m			
	BS EN 60669-1			
	CE Marked			
Module Size Height = 67mm Width = 67mm Depth = 22mm				



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

78CW10DPBK-B

Hartland CFX Black Nickel Wide Rocker I gang TOAX Double Pole Black Nickel/Black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:56 AM E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









