



Wiring Accessories • Smart Lighting Control • Wireless Audio

## 78CWRRTBK-B

Hartland CFX Black Nickel Wide Rocker 1 gang 10AX Push To Make/Push to Break Retractive Black Nickel/Black

Rem Image	HAITIAIIU GEA DIACK INICKEI WIDE R	ocker 1 gang 10AX Push To Make/Push to I	DIEAN NELIACTIVE DIACK NICKEI/DIACK
Primary Range	Item Image	Wiring	Dimensions
Primary Range	_	_	_
Insert Type		×	×
Insert Type			
Insert Type	D: D	U. H. 105V	
Plate Finish   Hartland CFX Black Nickel			
Insert Colour			
EAN13 Barcode 5051164021429  Commodity Code 85363010  Luckins TSI 453341153  ETIM Class EC001590  Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 25mm  Switched Poles Single  Current Rating 10AX  Voltage 2020/250V AC  Maximum Load 10 Amp inductive  Mains Frequency 50Hz  P Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm³  Terminal Capacity 1 3x2.5mm³  Earth Terminal Capacity 1 6x1mm³  Earth Terminal Capacity 1 6x1mm³  Earth Terminal Capacity 2 4x1.5mm³  Earth Terminal Capacity 3 2x2.5mm³  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 6 1x6mm²  Earth Terminal Capacity 7 1x4mm² Multi-strand  Earth Terminal Capacity 9 1x6mm²  Earth Terminal Capacity 9 1x6mm²  Earth Terminal Capacity 9 1x6mm²  Earth Terminal Capacity 1 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Earth Terminal Capacity 6 1x6mm²  Earth Terminal Capacity 6 1x6mm²  Earth Terminal Capacity 7 1x6mm²  Earth Terminal Capacity 8 1x6mm²  Earth Terminal Capacity 9 1x6mm²  Earth Terminal Capac			
Commodity Code         85363010           Luckins TSI         453341153           ETIM Class         EC001590           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Votage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Earth Terminal Capacity 6         1x6mm²           Earth Terminal Capacity 7         1x6mm²           Earth Terminal Capacity 8         1x6mm²			
Luckins TSI         453341153           ETIM Class         EC001590           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           For touch Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         20			
ETIM Class	-		
Dimensions (Nominal)   Single:   Height = 86.0mm   Width = 86.0mm   Depth = 5.0mm			
Box Fixing Hote Centres			
Minimum Wall Box Depth         25mm           Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked			
Switched Poles         Single           Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked	-		
Current Rating         10AX           Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked			
Voltage         220/250V AC           Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked			
Maximum Load         10 Amp inductive           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked	-		
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked			
Contact Gap Minimum 3mm  Terminal Capacity 1 3x2.5mm²  Terminal Capacity 2 1x4mm² Multi-strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 2x2.5mm²  Earth Terminal Capacity 3 1x4mm² Multi-strand  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Additional Notes CE Marked	Mains Frequency	·	
Terminal Capacity 1         3x2.5mm²           Terminal Capacity 2         1x4mm² Multi-strand           Terminal Capacity 3         1x6mm²           Earth Terminal Capacity 1         6x1mm²           Earth Terminal Capacity 2         4x1.5mm²           Earth Terminal Capacity 3         2x2.5mm²           Earth Terminal Capacity 4         1x4mm² Multi-strand           Earth Terminal Capacity 5         1x6mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS EN 60669-1           Additional Notes         CE Marked	IP Rating		
Terminal Capacity 2 1x4mm² Multi-strand  Terminal Capacity 3 1x6mm²  Earth Terminal Capacity 1 6x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 2x2.5mm²  Earth Terminal Capacity 4 1x4mm² Multi-strand  Earth Terminal Capacity 5 1x6mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Additional Notes CE Marked	Contact Gap Minimum	3mm	
Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Earth Terminal Capacity 5  Tx6mm²  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS EN 60669-1  Additional Notes  CE Marked	Terminal Capacity 1	3x2.5mm²	
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Terminal Capacity 2	1x4mm² Multi-strand	
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  Ax1.5mm²  2x2.5mm²  1x4mm² Multi-strand  1x4mm² Multi-strand  1x6mm²  1x6m	Terminal Capacity 3	1x6mm²	
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 5  1x6mm²  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  Additional Notes  2x2.5mm²  1x4mm² Multi-strand  1x6mm²  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  BS EN 60669-1  Additional Notes  CE Marked	Earth Terminal Capacity 1	6x1mm²	
Earth Terminal Capacity 4  Earth Terminal Capacity 5  1x6mm²  Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  Additional Notes  CE Marked	Earth Terminal Capacity 2	4x1.5mm²	
Earth Terminal Capacity 5  Product Class 1  Ambient Operating Temperature  Assimum Installation Altitude  Standard/Approval  Additional Notes  Must be earthed  Must be earthed  1x6mm²  Must be earthed  5° to +40°C  Recommended Location  Internal Use Only  BS EN 60669-1  CE Marked	Earth Terminal Capacity 3	2x2.5mm²	
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Additional Notes CE Marked		1x4mm² Multi-strand	
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS EN 60669-1  Additional Notes CE Marked		1x6mm²	
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS EN 60669-1       Additional Notes     CE Marked			
Maximum Installation Altitude     2000m       Standard/Approval     BS EN 60669-1       Additional Notes     CE Marked			
Standard/Approval BS EN 60669-1 Additional Notes CE Marked			
Additional Notes CE Marked			
Module Size Height = 67mm Width = 67mm Depth = 22mm			
	Module Size		



Wiring Accessories • Smart Lighting Control • Wireless Audio

## 78CWRRTBK-B

## Hartland CEX Black Nickel Wide Rocker 1 gang 104X Push To Make/Push to Break Retractive Black Nickel/Black

Hartianu CFA Diack Nickel Wide R	tocker i garig TUAN Push TO Make/Push to	DIEAK RELIACTIVE DIACK INICKEI/DIACK
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:56 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









