



## 7CBCUS99B

### Hartland CFX Copper Bronze 2 gang 13A Unswitched Socket Black

| Item Image                    | Wiring                                                                            | Dimensions                                                                          |
|-------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                               |  |  |
| Primary Range                 | Hartland CFX                                                                      |                                                                                     |
| Insert Type                   | 2 gang 13A Unswitched Socket                                                      |                                                                                     |
| Plate Finish                  | Hartland CFX Copper Bronze                                                        |                                                                                     |
| Insert Colour                 | Black                                                                             |                                                                                     |
| EAN13 Barcode                 | 5017504011413                                                                     |                                                                                     |
| Commodity Code                | 85363010                                                                          |                                                                                     |
| Luckins TSI                   | 402445386                                                                         |                                                                                     |
| ETIM Class                    | EC000125                                                                          |                                                                                     |
| Dimensions (Nominal)          | Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm                             |                                                                                     |
| Fixing Hole Centres           | Box Fixing = 120.6mm Grid Fixing = CFX Clips                                      |                                                                                     |
| Minimum Wall Box Depth        | 35mm                                                                              |                                                                                     |
| Switched Poles                | None                                                                              |                                                                                     |
| Current Rating                | 13 Amp                                                                            |                                                                                     |
| Voltage                       | 220/250V AC                                                                       |                                                                                     |
| Maximum Load                  | 13 Amp                                                                            |                                                                                     |
| Mains Frequency               | 50Hz                                                                              |                                                                                     |
| IP Rating                     | IP2XD                                                                             |                                                                                     |
| Contact Gap Minimum           | None                                                                              |                                                                                     |
| Terminal Capacity 1           | 3x2.5mm <sup>2</sup>                                                              |                                                                                     |
| Terminal Capacity 2           | 3x4mm <sup>2</sup>                                                                |                                                                                     |
| Terminal Capacity 3           | 2x6mm <sup>2</sup> Multi-strand                                                   |                                                                                     |
| Terminal Capacity 4           | 1x10mm <sup>2</sup>                                                               |                                                                                     |
| Earth Terminal Capacity 1     | 3x2.5mm <sup>2</sup>                                                              |                                                                                     |
| Earth Terminal Capacity 2     | 3 x 4mm <sup>2</sup>                                                              |                                                                                     |
| Earth Terminal Capacity 3     | 2 x 6mm <sup>2</sup> Multi-strand                                                 |                                                                                     |
| Earth Terminal Capacity 4     | 1 x 10mm <sup>2</sup>                                                             |                                                                                     |
| Product Class 1               | Must be earthed                                                                   |                                                                                     |
| Ambient Operating Temperature | -5° to +40°C                                                                      |                                                                                     |
| Recommended Location          | Internal Use Only                                                                 |                                                                                     |
| Maximum Installation Altitude | 2000m                                                                             |                                                                                     |
| Standard/Approval             | BS 1363-2                                                                         |                                                                                     |
| Additional Notes              | Shuttered: Yes                                                                    |                                                                                     |

**7CBCUS99B**

**Hartland CFX Copper Bronze 2 gang 13A Unswitched Socket Black**

|                                                                                                                                           |                                                                                                                                     |                                                                                                                                                                                 |
|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Patents and Trademarks                                                                                                                    | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445 |                                                                                                                                                                                 |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                               | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                       | Correct as at 05 July 2022 08:58 AM<br>E&OE                                                                                                                                     |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble**  
**LUCKINS**

