Hamilton

## making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio		
	7EBCDTVFB	
Hartland CFX Etrium	Bronze 1 gang Non-Isolated TV (Female) (D	AB Compatible) Black
Item Image	Wiring	Dimensions
		Hemilton HARTLAND CFX DTVF Non-Isolated TV (female)
	EVIC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable	
Primary Range	Hartland CFX	
Insert Type	1 gang Non-Isolated TV (female) (DAB Compatible)	
Plate Finish	Hartland CFX Etrium Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504011925	
Commodity Code	85367000	
Luckins TSI	398274072	
ETIM Class	S98274072	
	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Dimensions (Nominal)		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips 35mm	
Minimum Wall Box Depth	N/A	
Switched Poles	n/a	
Current Rating IP Rating	IP2XD	
Contact Gap Minimum	N/A 5x1mm <sup>2</sup>	
Earth Terminal Capacity 1		
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 5733. BS EN 50083-2: 2012/A1:2015. BS EN 61169-2:2007	
EuroFix Additional Notes	TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet	
Frequencies 1	TV DC=5-2200 MHz	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:58 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered	oad, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in STrimble product selector DSSPlus CER No. NA1128