

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7EBCWRRTBL-B

Hartland CFX Etrium Bronze Wide Rocker 1 gang 10AX Push To Make/Push to Break Retractive Black/Black

Primary Range	S		
Primary Range Hartland CFX Insert Type Wide Rocker - 1 gang 10AX Push To Make/Push to Break Retractive Rocker Plate Finish Hartland CFX Etrium Bronze Insert Colour Black/Black EAN13 Barcode 5051164021450 Commodity Code 85363010 Luckins TSI 453341353 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Insert Type			
Plate Finish Hartland CFX Etrium Bronze Insert Colour Black/Black EAN13 Barcode 5051164021450 Commodity Code 85363010 Luckins TSI 453341353 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Insert Colour			
EAN13 Barcode 5051164021450 Commodity Code 85363010 Luckins TSI 453341353 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Commodity Code 85363010 Luckins TSI 453341353 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Luckins TSI 453341353 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency IP Rating IP2XD	453341353		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD	25mm		
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD	Single		
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD			
Mains Frequency 50Hz IP Rating IP2XD	220/250V AC		
IP Rating IP2XD	10 Amp inductive		
·			
Contact Gap Minimum 3mm	IP2XD		
· · · · · · · · · · · · · · · · · · ·	3mm		
Terminal Capacity 1 3x2.5mm ²			
Terminal Capacity 2 1x4mm² Multi-strand	1x4mm² Multi-strand		
Terminal Capacity 3 1x6mm ²	1x6mm ²		
Earth Terminal Capacity 1 6x1mm ²	6x1mm²		
Earth Terminal Capacity 2 4x1.5mm ²	4x1.5mm²		
Earth Terminal Capacity 3 2x2.5mm ²	2x2.5mm²		
Earth Terminal Capacity 4 1x4mm² Multi-strand	1x4mm² Multi-strand		
Earth Terminal Capacity 5 1x6mm ²	1x6mm²		
Product Class 1 Must be earthed	Must be earthed		
Ambient Operating Temperature -5° to +40°C			
Recommended Location Internal Use Only			
Maximum Installation Altitude 2000m			
Standard/Approval BS EN 60669-1			
Additional Notes CE Marked			
Module Size Height = 67mm Width = 67mm Depth = 22mm			





making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7EBCWRRTBL-B

Hartland CEX Etrium Bronze Wide Rocker 1 gang 10AX Push To Make/Push to Break Retractive Black/Black

Hartialia CFA Ethath Biorize vide Rocker I gang TOAA Pash To Make/Pash to Bleak Retractive Black/Black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:59 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









