

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7HBCDTRIDB

Hartland CFX Connaught Bronze Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible) Black

Hartiand CFA Connaught Biorize Non-isolated 17+FM+5A1 Triplexer Till/Sout (DAB Compatible) Black		
Item Image	Wiring	Dimensions
	1. Undo the cable clamp screw. 2. If it up the cover of the clamp, be careful not to displace the control of the cable clamp screw. 3. Insert the conductor into the terminal side which is located in the casing of the modified. 4. Insert the conductor into the terminal side which is located in the casing of the modified. 5. Insert the conductor into the terminal side which is located in the casing of the modified. 6. Consider the conductor into the control position as shown below. 6. Consider the control of the modified into the control position is shown below. 6. Consider the control of the modified into the control position is shown below. 6. Consider the control of the control of the modified into the control of th	Hamilton HARTLAND CFX DTRID Non-Isolated Tv/FM/Satellite1 Triplexer 1in/3out
Primary Range	Hartland CFX	
Insert Type	Non-Isolated TV+FM+SAT Triplexer 1in/3out (DAB Compatible)	
Plate Finish	Hartland CFX Connaught Bronze	
Insert Colour	Black	
EAN13 Barcode	5017504012908	
Commodity Code	85367000	
Luckins TSI	398275149	
ETIM Class	EC000439	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
Current Rating	n/a	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm ²	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 50083-2:2012/A1; 2015. BS EN 61169-2:2007. BS EN 61169-24:2009	
EuroFix Additional Notes	Triplexer for use with combined TV FM and Satellite Signal (DAB compatible)	
Frequencies 1	TV=5-68 MHz 125-860 MHz	
Frequencies 2	FM=88-108 MHz	
Frequencies 3	SAT DC=950-2200 MHz	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:59 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84









