Hamilton

## making connections beautifully

	7400 1450	
	<u>71C2J45B</u>	
Hartland CFX P	olished Brass 2 gang RJ45 CAT 5E Outlet - U	Inshielded Black
Item Image	Wiring	Dimensions
	RJ45 CATSe Rear View	Example control of the control of t
Primary Range	Hartland CFX	
nsert Type	2 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Hartland CFX Polished Brass	
nsert Colour	Black	
EAN13 Barcode	5017504241582	
Commodity Code	85176990	
Luckins TSI	388235872	
ETIM Class	EC001264	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Veight	110 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Ainimum Wall Box Depth	35mm	
Switched Poles	N/A	
Current Rating	n/a	
P Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm <sup>2</sup>	
Earth Terminal Capacity 2	4x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-Strand	
Earth Terminal Capacity 5	1x6mm <sup>2</sup>	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Aaximum Installation Altitude	2000m	
Standard/Approval	N/A	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiriing schedules	
Patents and Trademarks	CAN be used in both Lik 300A and Lik 300B wining schedules CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:49 A E&C

SL