Hamilton

making connections beautifully

	Wiring Accessories •	Smart Lighting Control • Wireless Audio						
<u>71C2XTMPB-W</u>								
Hartland CFX Polished Brass 2x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Polished Brass/White								
Item Image	Wiring	Dimensions						
	Multi- Way Wiring using Slave module(s)	HEIRIFICATION HARTLAND CEX 2XTM Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer						
Primary Range	Hartland CFX							
Insert Type	2 gang 250W/210VA Resistive/Inductive Trailing Edge Touch	Master Multi-Way Dimmer						
Plate Finish	Hartland CFX Polished Brass							
Insert Colour	Polished Brass/White							
EAN13 Barcode	5017504009052							
Commodity Code	85363010							
Luckins TSI	391558931							
ETIM Class	EC000025							
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mn	2						
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	1						
Minimum Wall Box Depth	35mm							
Wattage	250W Resistive 210VA Inductive							
Switched Poles	N/A							
Current Rating	1.1 Amps per gang							
Voltage	220/250V AC							
Maximum Load	250W Resistive per gang 210VA Inductive Min Load 25W/25V	VA						
Mains Frequency	50Hz							
IP Rating	IP2XD							
Contact Gap Minimum	N/A							
Terminal Capacity 1	2x1mm ²							
Terminal Capacity 2	2x1.5mm ²							
Earth Terminal Capacity 1	5x1mm ²							
Earth Terminal Capacity 2	4 x 1.5mm2							
Earth Terminal Capacity 3	3 x 2.5mm2							
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand							
Earth Terminal Capacity 5	1 x 6mm2							
Product Class 1	Face plate must be earthed							
Ambient Operating Temperature	-5° to +40°C							
Recommended Location	Internal Use Only							
Maximum Installation Altitude	2000m							
Standard/Approval	BS EN 60669-2-1							
Additional Notes	TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for dimming low voltage electronic halogen transformers it must be transformer. Tungsten filament GU10 lamps must be branded dimmers should be de-rated by 25%. When dimming LED lar compatibility. When using mains voltage halogen load transfor switching a push to make retractive switch should be installed not work with this product)	be noted that the dimmer controls the primary side of the d with a fuse base. When using mains voltagehalogen lamps- mps de-rated by 75% - please contact our Technical for wrmer - maximum rating is 210VA. NOTE: For multi-way						

SL

Hamilton

making connections beautifully

CERT. No. FM11238

Wiring Accessories • Smart Lighting Control • Wireless Audio

71C2XTMPB-W

Hartland CFX Polished Brass 2x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Polished Brass/White

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Refere R21 = 3023446 SS2 =3023445	ence Nos.					
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.			It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings o of certain finishes.	of	Correct as at 05 July 2022 08:49 AM E&OE				
	ice 1 Rushmills, Bedford Road, Northampton NN4 7YB		-itish British Institute Of Interfor	Listed in STrimble.	riba product selector	ISO 9001 Quality Management	

SL