

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

71CBPS

Hartland CEX Polished Brass Single Blank Plate

Item Image Wiring Dimensions Haritand CFX Insert Type Insert Type Insert Type Single Blank Plate Plate Finish Haritand CFX Polished Brass Insert Colour No Insert Colour No Insert Colour EAN13 Barrode Commodity Code 74199100 Luckins TSI 388234967 ETIM Class Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 CR Shiring Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Contact Gap Minimum N/A Contact Gap Minimum N/A Contact Gap Minimum N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Fix6mm² Froduct Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Primary Range	
Insert Type	
Plate Finish Hartland CFX Polished Brass Insert Colour No Insert Colour EAN13 Barcode 5017504249885 Commodity Code 74199100 Luckins TSI 388234967 ETIM Class EC000018 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Insert Colour	
EAN13 Barcode 5017504249885 Commodity Code 74199100 Luckins TSI 388234967 ETIM Class EC000018 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Internal Use Only	
Commodity Code 74199100 Luckins TSI 388234967 ETIM Class EC000018 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Internal Use Only	
Luckins TSI 388234967 ETIM Class EC000018 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
ECIM Class Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Recommended Location Internal Use Only	
Dimensions (Nominal) Single: Height = 86.0mm	
Weight 142 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth Any Box N/A Current Rating IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Minimum Wall Box Depth Any Box Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tx4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Switched Poles N/A Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Recommended Location N/A N/A N/A N/A N/A N/A N/A Sx1mm² Sx1mm² 4x1.5mm² 1x4mm² 1x4mm² 1x4mm² 1x4mm² 1x6mm² Face plate must be earthed Recommended Location Internal Use Only	
Current Rating n/a IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Face plate must be earthed Recommended Location Internal Use Only	
IP Rating N/A Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Recommended Location N/A N/A N/A N/A N/A Sx1mm² 4x1.5mm² 1x4mm² 1x4mm² 1x4mm² 1x4mm² 1x6mm² Face plate must be earthed Recommended Location Internal Use Only	
Contact Gap Minimum N/A Earth Terminal Capacity 1 Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Recommended Location N/A 5x1mm² 4x1.5mm² 1x4mm² 1x4mm² Multi-strand Earth Terminal Capacity 5 Ix6mm² Face plate must be earthed Internal Use Only	
Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Earth Terminal Capacity 5 1x6mm² Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Product Class 1 Face plate must be earthed Recommended Location Internal Use Only	
Recommended Location Internal Use Only	
·	
Maximum Installation Altitude 2000m	
Standard/Approval N/A	
Additional Notes Plates must be Earthed via the Earth Tag.	
Patents and Trademarks Patents and Trademarks Patents and Trademarks Patents and Trademarks R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter design and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. B Hamilton & Co Ltd. Unit 10 Carrick Business Centre. 4-5 Bonyille Boad, Brislington, Bristol, BS4 5NZ	022 08:49 AM E&O

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmilts, Bedford Road, Northan Registered in London No. 941624 VAT Registration No

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











