

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

71CKELW

Hartland CFX Polished Brass 1 gang 20AX 2 Way Key switch EMG LTG TEST White

Item Image	Wiring	Dimensions		
EMG LTG TEST	Abernative 2 very westering	Hamilton HARTLAND CFX KEL 2 Way Key switch EMG LTG TEST		
Primary Range	Hartland CFX			
Insert Type	1 gang 20AX 2 Way Key Switch EMG LTG TEST			
Plate Finish	Hartland CFX Polished Brass			
Insert Colour	White			
EAN13 Barcode	5017504240103			
Commodity Code	85363030			
Luckins TSI	388235199			
ETIM Class	EC000029			
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0n	nm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips			
Minimum Wall Box Depth	25mm			
Switched Poles	Single			
Current Rating	20AX			
Voltage	220/250V AC			
Maximum Load	20 Amp inductive			
Mains Frequency	50Hz			
IP Rating	IP2XD			
Contact Gap Minimum	3mm			
Terminal Capacity 1	5 x1mm²			
Terminal Capacity 2	4x1.5mm²			
Terminal Capacity 3	2x2.5mm²			
Terminal Capacity 4	2x4mm² Multi-strand			
Terminal Capacity 5	1x6mm²			
Earth Terminal Capacity 1	6x1mm²			
Earth Terminal Capacity 2	5x1.5mm²			
Earth Terminal Capacity 3	3 x2.5mm²			
Earth Terminal Capacity 4	2x4mm² Multi-strand			
Earth Terminal Capacity 5	1x6mm²			
Product Class 1	Must be earthed			
Ambient Operating Temperature	-5° to +40°C			
Recommended Location	Internal Use Only			
Maximum Installation Altitude	2000m			
Standard/Approval	BS EN 60669-1			



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

71CKELW

Hartland CFX Polished Brass 1 gang 20AX 2 Way Key switch EMG LTG TEST White			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:50 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









