

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 71CR31PB-W

| Hartland CFX Polished Brass 1 gang 10AX Intermediate Rocker Polished Brass/White |  |                                      |  |  |
|--|--|--------------------------------------|--|--|
| Item Image   | Wiring   | Dimensions                           |  |  |
|  | 2 Way Switch Switch 2 Way Switch Light 2 Way Switch | Hariland CFX R31 Intermediate Rocker |  |  |
| Primary Range  | Hartland CFX   |                                      |  |  |
| Insert Type  | 1 gang 10AX Intermediate Rocker  |                                      |  |  |
| Plate Finish   | Hartland CFX Polished Brass  |                                      |  |  |
| Insert Colour  | Polished Brass/White   |                                      |  |  |
| EAN13 Barcode  | 5017504243319  |                                      |  |  |
| Commodity Code   | 85363010   |                                      |  |  |
| Luckins TSI  | 388235513  |                                      |  |  |
| ETIM Class   | EC001590   |                                      |  |  |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm   |                                      |  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |                                      |  |  |
| Minimum Wall Box Depth   | 25mm   |                                      |  |  |
| Switched Poles   | Single   |                                      |  |  |
| Current Rating   | 10AX   |                                      |  |  |
| Voltage  | 220/250V AC  |                                      |  |  |
| Maximum Load   | 10 Amp inductive   |                                      |  |  |
| Mains Frequency  | 50Hz   |                                      |  |  |
| IP Rating  | IP2XD  |                                      |  |  |
| Contact Gap Minimum  Terminal Capacity 1   | 3mm  |                                      |  |  |
|  | 5x1mm²   |                                      |  |  |
| Terminal Capacity 2 Terminal Capacity 3  | 4x1.5mm²   |                                      |  |  |
| Terminal Capacity 4  | 1x2.5mm²  1x4mm² Multi-strand  |                                      |  |  |
| Terminal Capacity 4  Terminal Capacity 5   | 1x6mm²   |                                      |  |  |
| Earth Terminal Capacity 1  | 5x1mm²   |                                      |  |  |
| Earth Terminal Capacity 2  | 4x1.5mm²   |                                      |  |  |
| Earth Terminal Capacity 3  | 3x2.5mm <sup>2</sup>   |                                      |  |  |
| Earth Terminal Capacity 4  | 1x4mm² Multi-strand  |                                      |  |  |
| Earth Terminal Capacity 5  | 1x6mm²   |                                      |  |  |
| Product Class 1  | Must be earthed  |                                      |  |  |
| Ambient Operating Temperature  | -5° to +40°C   |                                      |  |  |
| Recommended Location   | Internal Use Only  |                                      |  |  |
| Maximum Installation Altitude  | 2000m  |                                      |  |  |
| Standard/Approval  | BS EN 60669-1  |                                      |  |  |
|  | 1  |                                      |  |  |

SL

# making connections beautifully

# Wiring Accessories • Smart Lighting Control • Wireless Audio

#### 71CR31PB-W

## Hartland CFX Polished Brass 1 gang 10AX Intermediate Rocker Polished Brass/White

| Haltialid Of XT district blass T garig ToAX intermediate Nocker Folished blass/White  |   |  |
|---|---|--|
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                               | It is the policy of the company to improve products<br>as part of our development programme.  Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing   | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of  | Correct as at 05 July 2022 08:50 AM<br>E&OE  |

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









