




71CSPNPB-B

Hartland CFX Polished Brass 1 gang 13A Double Pole Fused Spur and Neon Polished Brass/Black

| Item Image | Wiring | Dimensions |
|---|---|---|
|  |  |  |
| Primary Range | Hartland CFX | |
| Insert Type | 1 gang 13A Double Pole Fused Spur + Neon | |
| Plate Finish | Hartland CFX Polished Brass | |
| Insert Colour | Polished Brass/Black | |
| EAN13 Barcode | 5017504242923 | |
| Commodity Code | 85369010 | |
| Luckins TSI | 388236017 | |
| ETIM Class | EC001590 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Weight | 190 GR | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| Current Rating | 13 Amp | |
| Voltage | 220/250V AC | |
| Maximum Load | 13 Amp | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3x2.5mm² | |
| Terminal Capacity 2 | 2x4mm² Multi-Strand | |
| Terminal Capacity 3 | 1x6mm² | |
| Earth Terminal Capacity 1 | 6x1mm² | |
| Earth Terminal Capacity 2 | 5x1.5mm² | |
| Earth Terminal Capacity 3 | 3x2.5mm² | |
| Earth Terminal Capacity 4 | 2x4mm² Multi-Strand | |
| Earth Terminal Capacity 5 | 1x6mm² | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 1363-4 | |

71CSPNPB-B

Hartland CFX Polished Brass 1 gang 13A Double Pole Fused Spur and Neon Polished Brass/Black

| | | |
|---|---|---|
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 08:50 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble**
LUCKINS

