

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7PNCSHSW

Hartland CFX Polished Nickel Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Primary Range Hartland CFX Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Hartland CFX Vertical Polished Nickel Insert Colour White EAN13 Barcode Software	s		
Insert Type			
Plate Finish			
Plate Finish			
EAN13 Barcode 5017504077518 Commodity Code 85363010 Luckins TSI 402446961 ETIM Class EC000186 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Commodity Code 85363010 Luckins TSI 402446961 ETIM Class EC000186 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Luckins TSI 402446961 ETIM Class EC000186 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Luckins TSI 402446961 ETIM Class EC000186 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
ETIM Class EC000186 Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Dimensions (Nominal) Double: Height = 145.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²	·		
Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 3 3x2.5mm² Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 4 2x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²			
Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²	2x4mm² Multi-strand		
Earth Terminal Capacity 1 9x1mm² Earth Terminal Capacity 2 6x1.5mm²	1x6mm²		
Earth Terminal Capacity 2 6x1.5mm ²	9x1mm²		
···			
⊑arti remiinai ∪apacity σ 4xz.3πiπ⁴	4x2.5mm²		
Earth Terminal Capacity 4 2x4mm² Multi-strand	2x4mm² Multi-strand		
Earth Terminal Capacity 5 1x6mm ²			
Product Class 1 Must be earthed			
Ambient Operating Temperature -5° to +40°C			
Recommended Location Internal Use Only			
Maximum Installation Altitude 2000m			
Standard/Approval BS EN 61558-2-5 + BS 4573			
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm			





making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7PNCSHSW

Hartland CEX Polished Nickel Shaver Dual Voltage Unswitched Socket (Vertically Mounted) White

Hartiand CFA Polished Nickel Shaver Dual Voltage Unswitched Socket (Vertically Mounted) white			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 05 July 2022 09:00 AM	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









