

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## **7PNCUS5B**

Hartland CFX Polished Nickel 1 gang 5A Unswitched Socket Black

Primary Range	Item Image	Wiring	Dimensions	
Insert Type		Neutral Earth	US5 Unswitched Socket	
Plate Finish   Hartland CFX Polished Nickel   Insert Colour   Black   EAN13 Barcode   5017504077662   Commodity Code   85363010   Luckins TSI   402448642   ETIM Class   EC000125   Dimensions (Nominal)   Single: Height = 86.0mm   Width = 86.0mm   Depth = 5.0mm   Weight   150 GR   Fixing Hole Centres   Box Fixing = 60.3mm   Grid Fixing = CFX Clips   Minimum Wall Box Depth   35mm   Switched Poles   None   Current Rating   5 Amp   Voltage   220/250V AC   Maximum Load   5 Amp   Mains Frequency   50Hz   PRating   1P2XD   Contact Gap Minimum   None   Terminal Capacity 1   5 x1mm²   Terminal Capacity 1   5 x1mm²   Terminal Capacity 3   22.6mm²   Earth Terminal Capacity 4   1x4mm²   Earth Terminal Capacity 4   1 x4mm²   Earth Terminal Capacity 5   5 x5 x440°C   Recommended Location   Internal Use Only   Maximum Instalation Altitude   2000m   Standard/Approval   B S 546	Primary Range	Hartland CFX		
Insert Colour Black EAN13 Barcode 5017504077662 Commodity Code 85363010 Luckins TSI 402448642 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Walns Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 2x2.5mm2 Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 5 1x1mm² Earth Terminal Capacity 6 1x4mm² Earth Terminal Capacity 6 1x4mm² Earth Terminal Capacity 7 1x4mm² Earth Terminal Capacity 8 1x4mm² Earth Terminal Capacity 9 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 2x2.5mm2 Earth Terminal Capacity 4 1x4mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5* 10 +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m	Insert Type	1 gang 5A Unswitched Socket		
EAN13 Barcode 5017504077662  Commodity Code 85363010  Luckins TSI 402448642  ETIM Class EC000125  Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm  Weight 150 GR  Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips  Minimum Wall Box Depth 35mm  Switched Poles None  Current Rating 5.4mp  Voltage 220/250V AC  Maximum Load 5.4mp  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum None  Terminal Capacity 1 5.x1mm²  Terminal Capacity 1 5.x1mm²  Terminal Capacity 3 4x1.5mm²  Terminal Capacity 4 1x4mm²  Earth Terminal Capacity 4 5x1mm²  Earth Terminal Capacity 2 4x1.5mm²  Earth Terminal Capacity 3 2x2.5mm²  Earth Terminal Capacity 4 1x4mm²  Earth Terminal Capacity 5 1x4mm²  Earth Terminal Capacity 6 1x4mm²  Earth Terminal Capacity 7 5x1mm²  Earth Terminal Capacity 8 2x2.5mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 3 2x2.5mm²  Earth Terminal Capacity 4 1x4mm²  Farth Terminal Capacity 5 1x4mm²  Earth Terminal Capacity 6 1x4mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 1x4mm²  Earth Terminal Capacity 3 1x4mm²  Earth Terminal Capacity 6 1x4mm²  Earth Terminal Capacity 9 1x4mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 1 5x1				
Commodity Code         85363010           Luckins TSI         402448642           ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         150 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x4mm²           Earth Terminal Capacity 4         1 x4mm²           Earth Terminal Capacity 4         1 x4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature	Insert Colour	Black		
Luckins TSI         402448642           ETIM Class         EC000125           Dimensions (Nominal)         Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm           Weight         150 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Earth Terminal Ca	EAN13 Barcode			
ETIM Class	Commodity Code			
Dimensions (Nominal)   Single: Height = 86.0mm   Width = 86.0mm   Depth = 5.0mm	Luckins TSI			
Weight         150 GR           Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Maximum Evenercy         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5" to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         88 546	ETIM Class			
Fixing Hole Centres         Box Fixing = 60.3mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Dimensions (Nominal)			
Minimum Wall Box Depth         35mm           Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Weight			
Switched Poles         None           Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Fixing Hole Centres			
Current Rating         5 Amp           Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Farth Terminal Capacity 4         1 x 4mm²           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         85 546	Minimum Wall Box Depth			
Voltage         220/250V AC           Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Farth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Switched Poles	None		
Maximum Load         5 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Current Rating			
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Voltage	220/250V AC		
IP Rating	Maximum Load	5 Amp		
Contact Gap Minimum         None           Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm²           Earth Terminal Capacity 3         2 x 2.5mm²           Earth Terminal Capacity 4         1 x 4mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Mains Frequency	50Hz		
Terminal Capacity 1         5 x1mm²           Terminal Capacity 2         4x1.5mm²           Terminal Capacity 3         2x2.5mm²           Terminal Capacity 4         1x4mm²           Earth Terminal Capacity 1         5x1mm²           Earth Terminal Capacity 2         4 x 1.5mm2           Earth Terminal Capacity 3         2 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	IP Rating	IP2XD		
Terminal Capacity 2 4x1.5mm²  Terminal Capacity 3 2x2.5mm²  Terminal Capacity 4 1x4mm²  Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 2 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 546	Contact Gap Minimum	None		
Terminal Capacity 3  2x2.5mm²  Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  Example  2x2.5mm²  2x 2.5mm²  2x 2.5mm²  1x 4mm²  1x 4mm	Terminal Capacity 1	5 x1mm²		
Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  Standard/Approval  Internal Use Only  BS 546	Terminal Capacity 2	4x1.5mm <sup>2</sup>		
Earth Terminal Capacity 1 5x1mm²  Earth Terminal Capacity 2 4 x 1.5mm2  Earth Terminal Capacity 3 2 x 2.5mm2  Earth Terminal Capacity 4 1 x 4mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 546	Terminal Capacity 3	2x2.5mm²		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Terminal Capacity 4	1x4mm²		
Earth Terminal Capacity 3         2 x 2.5mm2           Earth Terminal Capacity 4         1 x 4mm2           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 546	Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 4 1 x 4mm2  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 546	Earth Terminal Capacity 2	4 x 1.5mm2		
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 546	Earth Terminal Capacity 3	2 x 2.5mm2		
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 546	Earth Terminal Capacity 4	1 x 4mm2		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS 546	Product Class 1	Must be earthed		
Maximum Installation Altitude2000mStandard/ApprovalBS 546	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 546	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
Additional Nation	Standard/Approval	BS 546		
Additional notes Snuttered: Yes Snuttered: Yes	Additional Notes	Shuttered: Yes		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## **7PNCUS5B**

Hartland CFX Polished Nickel 1 gang 5A Unswitched Socket Black				
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 09:01 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









