



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7PNCW10DPBC-B

Primary Range	Hartland CFX Polished Nickel Wide Rocker 1 gang 10AX Double Pole Bright Chrome/Black				
Primary Range	Item Image	Wiring	Dimensions		
Primary Range					
Insert Type		×	×		
Insert Type		_	_		
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Insert Type					
Plate Finish	Primary Range	Hartland CFX			
Insert Colour	Insert Type	Wide Rocker - 1 gang 10AX Double Pole Rocker			
EAN13 Barcode 5051164009984 Commodity Code 85363010 Luckins TS1 453341430 ETTM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x.2 5mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 5x4mm² Multi-strand Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm² Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 1x6mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Ca	Plate Finish	Hartland CFX Polished Nickel			
Commodity Code 85363010 Luckins TSI 453341430 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 6 1x6mm² <td>Insert Colour</td> <td colspan="2">Bright Chrome/Black</td>	Insert Colour	Bright Chrome/Black			
Luckins TSI 453341430 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/2560/ AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Inter					
ETIM Class					
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	Luckins TSI				
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm²		111 111			
Minimum Wall Box Depth 25mm Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Switched Poles Double Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	·				
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 5x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature 5-5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked		·			
Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Terminal Capacity 2					
Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes Ax1.5mm² 2x2.5mm² 1x4mm² Multi-strand 1x4mm² Multi-strand 1x6mm² 1x6m					
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm² Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes 2x2.5mm² 1x4mm² Multi-strand 1x6mm² Must be earthed -5° to +40°C Recommended Location Internal Use Only BS EN 60669-1 Additional Notes CE Marked					
Earth Terminal Capacity 4					
Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Standard/Approval BS EN 60669-1 Additional Notes CE Marked					
Additional Notes CE Marked					
wodule Size Height = 6/mm Width = 6/mm Depth = 22mm					
	INIOQUIE SIZE	Height = 6/mm Wiath = 6/mm Depth = 22mm			



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7PNCW10DPBC-B

Hartland CEX Polished Nickel Wide Rocker 1 gang 10AX Double Pole Bright Chrome/Black

Hartiand CFA Polished Nickel Wide Rockel 1 gang 10AA Double Pole bright Chrome/black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 05 July 2022 09:01 AM	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









