

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7RBC3XLEDITB100

Hartland CFX Richmond Bronze 3g 100W LED 2 Way Push On/Off Rotary Dimmer Richmond Bronze

Item Image	Wiring	Dimensions	
		HARTLAND CFX SALEDITE LEDITB100 2 Way Dimmer	
Primary Range	Hartland CFX		
Insert Type	3 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Plate Finish	Hartland CFX Richmond Bronze		
Insert Colour	Richmond Bronze		
EAN13 Barcode	5017504080167		
Commodity Code	85365015		
Luckins TSI	403364194		
ETIM Class	EC000025		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	5-70W Per Gang		
Switched Poles	Single		
Current Rating	0.3A Per Gang		
Voltage	230V AC		
Maximum Load	5-70W Per Gang		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm²		
Terminal Capacity 2	2X1.5mm²		
Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 2	4X1.5mm²		
Earth Terminal Capacity 3	3X2.5mm <sup>2</sup>		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Trailing Edge & Leading Edge Dimmer		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 7RBC3XLEDITB100

Hartland CFX Richmond Bronze 3g 100W LED 2 Way Push On/Off Rotary Dimmer Richmond Bronze			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 09:01 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









