

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## **7RBCDSATB**

Hartland CFX Richmond Bronze 1 gang Non-Isolated Digital Satellite (DAB Compatible) Black

| Item Image  | Wiring   | Dimensions   |
|---|--|--|
|   | EMC Gasket  Conductor Terminal Screw  Correct position of conductor, screening braid and cable                                       | Hartland CFX DSAT Non-isolated Satellite   |
| Primary Range   | Hartland CFX   |  |
| Insert Type   | 1 gang Non-Isolated Satellite (DAB Compatible)   |  |
| Plate Finish  | Hartland CFX Richmond Bronze   |  |
| Insert Colour   | Black  |  |
| EAN13 Barcode   | 5017504014513  |  |
| Commodity Code  | 85367000   |  |
| Luckins TSI   | 398319791  |  |
| ETIM Class  | EC000439   |  |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips  |  |
| Minimum Wall Box Depth  | 35mm   |  |
| Switched Poles  | N/A  |  |
| Current Rating  | n/a  |  |
| IP Rating   | IP2XD  |  |
| Contact Gap Minimum   | N/A  |  |
| Earth Terminal Capacity 1   | 5x1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2   | 4 x 1.5mm2   |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2   |  |
| Earth Terminal Capacity 4   | 1 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 5   | 1 x 6mm2   |  |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |  |
| Ambient Operating Temperature   | -5° to +40°C   |  |
| Recommended Location  | Internal Use Only  |  |
| Maximum Installation Altitude   | 2000m  |  |
| Standard/Approval   | BS 5733. BS EN 50083-2:2012/A1; 2015. BS EN 61169-24:2009.   |  |
| Frequencies 1   | SAT DC=5-2200 MHz  |  |
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 = 3023445 |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                                | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                        | Correct as at 05 July 2022 09:01 AM E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered office 1 Rushmilts, Bedford Road, Northan Registered in London No. 941624 VAT Registration N

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









