

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7RBCUS5B

Hartland CFX Richmond Bronze 1 gang 5A Unswitched Socket Black

Primary Rango	Item Image	Wiring	Dimensions	
Insert Type		Neutral Earth	US5 Unswitched Socket	
Plate Finish Hartland CFX Richmond Bronze Insert Colour Black EAN13 Barcode 5017504014940 Commodity Code 85383010 Luckins TSI 398320599 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz PR ating 1P2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 4 1 x4mm² Earth Terminal Capacity 5 5 x1mm² Earth Terminal Capacity 6 1 x4mm² Earth Terminal Capacity 7 5 x1mm² Earth Terminal Capacity 8 1 x4mm² Earth Terminal Capacity 9 1 x4mm² Earth Terminal Capacity 1 5 x1mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x4mm² Earth Terminal Capacity 5 5 x4m² Earth Terminal Capacity 6 1 x4mm² Earth Terminal Capacity 7 1 x4mm² Earth Terminal Capacity 8 1 x4mm² Earth Terminal Capacity 9 1 x4mm² Earth Terminal Capacity 1 1 x4mm² Earth Terminal Capacity 1 1 x4mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x4mm² Earth Terminal Capacity 5 1 x4mm² Earth Terminal Capacity 6 1 x4mm² Earth Terminal Capacity 6 1 x4mm² Earth Terminal Capacity 8 1 x4mm² Earth Terminal Capacity 9	Primary Range	Hartland CFX		
Insert Colour	Insert Type	1 gang 5A Unswitched Socket		
EAN13 Barcode 5017504014940 Commodity Code 85363010 Luckins TSI 398320599 ETIM Class EC000125 Dimensions (Nominal) Single: Helght = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 200250V AC Maximum Load 5 Amp Wains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Creminal Capacity 1 5x1mm² Terminal Capacity 1 5x1mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 4 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 5x1mm² Earth Terminal Capacity 5x1mm² Earth Terminal Capacity 6x1mm² Earth Terminal Capacity 6x1mm² Earth Terminal Capacity 7x1mm² Earth Terminal Capacity 8x1mm² Earth Terminal Capacity 9x1mm² Earth Terminal Capacity 9x				
Commodity Code 85363010 Luckins TSI 398320599 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 4 <	Insert Colour			
Luckins TSI 398320599 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 xtmm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capaci	EAN13 Barcode			
ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x2.5mm² Earth Terminal Capacity 4 1 x 4mm² For the 40°C Recommended Location Intension Mittude	Commodity Code			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/2560 VAC Maximum Load 5 Amp Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5" to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m St	Luckins TSI			
Weight 150 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Maximum Load 5 Mmp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm² Farth Terminal Capacity 4 1 x 4mm² Farth Terminal Capacity 5 5 to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	ETIM Class			
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Dimensions (Nominal)			
Minimum Wall Box Depth 35mm Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1 x4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Weight			
Switched Poles None Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Fixing Hole Centres			
Current Rating 5 Amp Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Farth Terminal Capacity 4 1 x 4mm² Farth Terminal Capacity 4 1 x 4mm² Rearth Terminal Capacity 5 0 x 2.5mm² Earth Terminal Capacity 6 1 x 4mm² Farth Terminal Capacity 7 1 x 4mm² Earth Terminal Capacity 8 2 x 2.5mm² Earth Terminal Capacity 9 1 x 4mm² Earth Terminal Capac	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Switched Poles	None		
Maximum Load 5 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Current Rating	5 Amp		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Voltage	220/250V AC		
IP Rating	Maximum Load	5 Amp		
Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Mains Frequency	50Hz		
Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	IP Rating	IP2XD		
Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Contact Gap Minimum	None		
Terminal Capacity 3 Zx2.5mm² Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Earth Terminal Capacity 4 Ix 4mm2 Product Class 1 Must be earthed Internal Use Only BS 546	Terminal Capacity 1	5 x1mm²		
Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 4mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Internal Use Only BS 546	Terminal Capacity 2	4x1.5mm ²		
Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Terminal Capacity 3	2x2.5mm²		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Terminal Capacity 4	1x4mm²		
Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 2	4 x 1.5mm2		
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 3	2 x 2.5mm2		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 4	1 x 4mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Product Class 1	Must be earthed		
Maximum Installation Altitude2000mStandard/ApprovalBS 546	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 546	Recommended Location			
· · · · · · · · · · · · · · · · · · ·	Maximum Installation Altitude	2000m		
Additional Notes Shuttered: Ves	Standard/Approval	BS 546		
Official Policy	Additional Notes	Shuttered: Yes		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7RBCUS5B

Hartland C	FX Richmond Bronze 1 gang 5A Unswitched S	Socket Black
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within	Due to manufacturing processes we cannot	Correct as at 05 July 2022 09:01 AM

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









