




72CJ45B

Hartland CFX Satin Brass 1 gang RJ45 CAT 5E Outlet - Unshielded Black

Item Image	Wiring	Dimensions
	 <p>RJ45 CAT5e and CAT6 Wiring Colour Codes</p> <p>Please always check with the colour coding found on the product.</p>	 <p>Hamilton® HARTLAND CFX</p> <p>J45 1 gang RJ45 -CAT 5E Outlet Unshielded 8 wire</p>
Primary Range	Hartland CFX	
Insert Type	1 gang RJ45 CAT 5E Outlet - Unshielded	
Plate Finish	Hartland CFX Satin Brass	
Insert Colour	Black	
EAN13 Barcode	5017504251574	
Commodity Code	85176990	
Luckins TSI	388237249	
ETIM Class	EC001264	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Weight	79 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	N/A	
Current Rating	n/a	
IP Rating	IP2XD	
Contact Gap Minimum	N/A	
Earth Terminal Capacity 1	5x1mm ²	
Earth Terminal Capacity 2	4x1.5mm ²	
Earth Terminal Capacity 3	3x2.5mm ²	
Earth Terminal Capacity 4	1 x 4mm ² Multi-Strand	
Earth Terminal Capacity 5	1x6mm ²	
Product Class 1	Must be earthed (ref BS7671 415.2.1)	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	N/A	
EuroFix Additional Notes	Can be used in both EIA 568A and EIA 568B wiring schedules	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2=3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	
It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	Correct as at 05 July 2022 08:51 AM E&OE	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	