

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

72CRRTSB-B

Primary Range	Hartland CFX Satin Brass 1 gang 10AX Push To Make/Push to Break Retractive Rocker Satin Brass/Black				
Insert Type		Wiring	Dimensions Hamilton HARTLAND CFX CFXRRT Push to Make/Push to Break Retractive Rocker		
Plate Finish Hartland CFX Satin Brass Insert Colour Satin Brass/Black EAN13 Barcode 5017504252199 Commodity Code 85363010 Luckins TSI 388236334 ETIM Class EC001590 Dimensions (Moninal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Single Single Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 4x4.5mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 4x4.5mm² Earth Terminal Capacity 7 4x4.5mm² Earth Terminal Capacity 8 4x4.5mm² Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² Multi-strand Earth Terminal Capacity 1 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x4mm² Multi-strand Earth Terminal Capacity 8 1x4mm² Multi-strand Earth Terminal Capacity 9 1x4mm² Multi-st	Primary Range	Hartland CFX			
Insert Colour	Insert Type	1 gang 10AX Push To Make/Push to Break Retractive Rock			
EAN13 Barcode 5017504252199 Commodity Code 85363010 Luckins TSI 388236334 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 1 5x1mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Froduct Class 1 Must be earthed Ambient Operating Temperature	Plate Finish	Hartland CFX Satin Brass	9 0		
Commodity Code 85363010 Luckins TSI 388236334 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Maximum Load 10 Amp inductive Maximum Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x/mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Ternth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand <td< td=""><td>Insert Colour</td><td>Satin Brass/Black</td><td colspan="3"></td></td<>	Insert Colour	Satin Brass/Black			
Luckins TSI 388236334 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand	EAN13 Barcode	5017504252199			
ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm²	Commodity Code	85363010			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed <tr< td=""><td>Luckins TSI</td><td>388236334</td><td colspan="3"></td></tr<>	Luckins TSI	388236334			
Weight 180 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal	ETIM Class				
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Dimensions (Nominal)				
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Weight				
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Fixing Hole Centres				
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C					
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Switched Poles	Single			
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Current Rating	-			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Voltage	220/250V AC			
IP Rating	Maximum Load				
Contact Gap Minimum 3mm Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Mains Frequency				
Terminal Capacity 1 5x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	IP Rating				
Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Ambient Operating Temperature 4x1.5mm² Must be earthed -5° to +40°C	Contact Gap Minimum				
Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 1x2.5mm² Terminal Capacity 4 1x4mm² Multi-strand Terminal Capacity 5 1x6mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 3x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Ambient Operating Temperature 4x1.5mm² Must be earthed -5° to +40°C	Terminal Capacity 1	5x1mm²			
Terminal Capacity 4 1x4mm² Multi-strand 1x6mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Must be earthed Ambient Operating Temperature 1x4mm² Multi-strand Must be earthed -5° to +40°C		4x1.5mm²			
Terminal Capacity 5	Terminal Capacity 3	1x2.5mm²			
Terminal Capacity 5	Terminal Capacity 4	1x4mm² Multi-strand			
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature 4x1.5mm² 1x4mm² Multi-strand 1x4mm² Multi-strand Must be earthed -5° to +40°C		1x6mm²			
Earth Terminal Capacity 3 Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Ambient Operating Temperature 3x2.5mm² 1x4mm² Multi-strand 1x6mm² Must be earthed -5° to +40°C	Earth Terminal Capacity 1	5x1mm²			
Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 2	4x1.5mm²			
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 3	3x2.5mm²			
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 4	1x4mm² Multi-strand			
Ambient Operating Temperature -5° to +40°C	Earth Terminal Capacity 5	1x6mm²	1x6mm²		
	Product Class 1	Must be earthed			
Recommended Location Internal Use Only	Ambient Operating Temperature	-5° to +40°C			
	Recommended Location	Internal Use Only			
Maximum Installation Altitude 2000m	Maximum Installation Altitude				
Standard/Approval BS EN 60669-1	Standard/Approval	BS EN 60669-1			



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

72CRRTSB-B

Hartland CFX Satin Brass 1 gang 10AX Push To Make/Push to Break Retractive Rocker Satin Brass/Black

Translatid of A Gatti Brass 1 garig 10/A/C1 doi: 10 Wake/1 doi: 10 Break Netraetive Nocker Gatti Brass/Black			dollye Rooker Gallii Diass/Diack
	Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
	All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
	Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:51 AM E&OE

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









