




## 72CSS1SB-W

Hartland CFX Satin Brass 1 gang 13A Double Pole Switched Socket Satin Brass/White

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|  |  |  |
| Primary Range   | Hartland CFX  |   |
| Insert Type   | 1 gang 13A Double Pole Switched Socket  |   |
| Plate Finish  | Hartland CFX Satin Brass  |   |
| Insert Colour   | Satin Brass/White   |   |
| EAN13 Barcode   | 5017504253011   |   |
| Commodity Code  | 85363010  |   |
| Luckins TSI   | 388237472   |   |
| ETIM Class  | EC000125  |   |
| Dimensions (Nominal)  | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm                              |   |
| Weight  | 180 GR  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = CFX Clips                                       |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Switched Poles  | Double  |   |
| Current Rating  | 13 Amp  |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 13 Amp  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 4x2.5mm²  |   |
| Terminal Capacity 2   | 3x4mm²  |   |
| Terminal Capacity 3   | 2x6mm² Multi-Strand   |   |
| Terminal Capacity 4   | 1x10mm²   |   |
| Earth Terminal Capacity 1   | 4x2.5mm²  |   |
| Earth Terminal Capacity 2   | 3x4mm²  |   |
| Earth Terminal Capacity 3   | 2x6mm² Multi-Strand   |   |
| Earth Terminal Capacity 4   | 1x10mm²   |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS 1363-2   |   |
| Additional Notes  | Dual Earth: Yes   |   |

## **72CSS1SB-W**

### **Hartland CFX Satin Brass 1 gang 13A Double Pole Switched Socket Satin Brass/White**

|   |   |   |
|---|---|---|
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445 |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                               | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                       | Correct as at 05 July 2022 08:51 AM<br>E&OE   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: [info@hamilton-litestat.com](mailto:info@hamilton-litestat.com) [www.hamilton-litestat.com](http://www.hamilton-litestat.com)

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble**  
**LUCKINS**



CERT. No. FM11238