

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

## 72CSS2SB-B

Hartland CFX Satin Brass 2 gang 13A Double Pole Switched Socket Satin Brass/Black

Primary Range	Item Image	Wiring	Dimensions	
Insert Type		Neutral Earth	Hemilton HARTLAND CFX SS2 Switched Socket	
Plate Finish	Primary Range	Hartland CFX		
Insert Colour Satin Brass/Black EAN13 Barcode 5017504250211 Commodity Code 85363010 Luckins TSI 388237508 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Wirdth = 145.0mm Depth = 5.0mm Weight 275 GR Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles Double Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Walns Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 4x2.5mm² Terminal Capacity 1 3x4mm² Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 5 2x6mm² Multi-Strand Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Earth Terminal Capacity 5 1x10m² Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval	Insert Type	2 gang 13A Double Pole Switched Socket		
EAN13 Barcode         5017504252021           Commodity Code         85363010           Luckins TSI         388237508           ETIM Class         EC000125           Dimensions (Nominal)         Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm           Weight         275 GR           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           For Horduct Class 1         Must be earthed <t< td=""><td>Plate Finish</td><td>Hartland CFX Satin Brass</td><td></td></t<>	Plate Finish	Hartland CFX Satin Brass		
Commodify Code         85363010           Luckins TSI         388237508           ETIM Class         EC000125           Dimensions (Nominal)         Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm           Weight         275 GR           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Cap	Insert Colour	Satin Brass/Black		
Luckins TSI         388237508           ETIM Class         EC000125           Dimensions (Nominal)         Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm           Weight         275 GR           Fixing Hole Centres         Box Fixing = 120.6mm Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Ter	EAN13 Barcode	5017504252021		
ETIM Class	Commodity Code	85363010		
Dimensions (Nominal)   Double: Height = 86.0mm   Width = 145.0mm   Depth = 5.0mm	Luckins TSI	388237508		
Weight         275 GR           Fixing Hole Centres         8ox Fixing = 120.6mm         Grid Fixing = CFX Clips           Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Froduct Class 1         Must be earthed           Ambient Operating Temperature         -5" to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m	ETIM Class	EC000125		
Fixing Hole Centres	Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0m	nm	
Minimum Wall Box Depth         35mm           Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Weight	275 GR		
Switched Poles         Double           Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating         13 Amp           Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 4         1x10mm²           Forduct Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40° C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Minimum Wall Box Depth	35mm		
Voltage         220/250V AC           Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Switched Poles	Double		
Maximum Load         13 Amp           Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Current Rating	13 Amp		
Mains Frequency         50Hz           IP Rating         IP2XD           Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Voltage	220/250V AC		
IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 4x2.5mm²  Terminal Capacity 2 3x4mm²  Terminal Capacity 3 2x6mm² Multi-Strand  Terminal Capacity 4 1x10mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Maximum Load	13 Amp		
Contact Gap Minimum         3mm           Terminal Capacity 1         4x2.5mm²           Terminal Capacity 2         3x4mm²           Terminal Capacity 3         2x6mm² Multi-Strand           Terminal Capacity 4         1x10mm²           Earth Terminal Capacity 1         4x2.5mm²           Earth Terminal Capacity 2         3x4mm²           Earth Terminal Capacity 3         2x6mm² Multi-Strand           Earth Terminal Capacity 4         1x10mm²           Product Class 1         Must be earthed           Ambient Operating Temperature         -5° to +40°C           Recommended Location         Internal Use Only           Maximum Installation Altitude         2000m           Standard/Approval         BS 1363-2	Mains Frequency	50Hz		
Terminal Capacity 1 4x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-Strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 4x2.5mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 2x6mm² Multi-Strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 2 3x4mm² Earth Terminal Capacity 2 Earth Terminal Capacity 3 2x6mm² Multi-Strand Earth Terminal Capacity 4 1x10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval  BS 1363-2	Contact Gap Minimum	3mm		
Terminal Capacity 3  Zx6mm² Multi-Strand  Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  Zx6mm² Multi-Strand  1x10mm²  1x10mm	Terminal Capacity 1	4x2.5mm²		
Terminal Capacity 4  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Maximum Installation Altitude  Standard/Approval  Standard/Approval  Internal Use Only  BS 1363-2	Terminal Capacity 2	3x4mm²		
Earth Terminal Capacity 1 4x2.5mm²  Earth Terminal Capacity 2 3x4mm²  Earth Terminal Capacity 3 2x6mm² Multi-Strand  Earth Terminal Capacity 4 1x10mm²  Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Terminal Capacity 3	2x6mm² Multi-Strand		
Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 4  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval	Terminal Capacity 4	1x10mm²		
Earth Terminal Capacity 3  Earth Terminal Capacity 4  Product Class 1  Ambient Operating Temperature  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  2x6mm² Multi-Strand  1x10mm²  Must be earthed  -5° to +40°C  Recommended Location  Internal Use Only  Standard/Approval  BS 1363-2	Earth Terminal Capacity 1	4x2.5mm²		
Earth Terminal Capacity 4 1x10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 2	3x4mm²		
Product Class 1 Must be earthed  Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 3	2x6mm² Multi-Strand		
Ambient Operating Temperature -5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 1363-2	Earth Terminal Capacity 4	1x10mm²		
Recommended Location     Internal Use Only       Maximum Installation Altitude     2000m       Standard/Approval     BS 1363-2	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 1363-2	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
[	Standard/Approval	BS 1363-2		
Additional Notes   Dual Earth: Yes	Additional Notes	Dual Earth: Yes		



making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## 72CSS2SB-B

## Hartland CEX Satin Brass 2 gang 13A Double Pole Switched Socket Satin Brass/Black

Hartiariu CFA Satiri Brass 2 garig 13A Double Pole Switched Socket Satiri Brass/Black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:51 AM E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









