

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio


72CUS2W

Hartland CFX Satin Brass 1 gang 2A Unswitched Socket White


Item Image



Wiring



Dimensions



Insert Type 1 gang 2A Unswitched Socket Plate Finish Hartland CFX Satin Brass Insert Colour White EAN13 Barcode 5017504250041 Commodity Code 85363010 Luckins TSI 388237698 ETIM Class ECO00125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Pixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 xtmm² Terminal Capacity 2 4t.5mm² Terminal Capacity 3 2x.2.5mm² Earth Terminal Capacity 4 1x.4mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1x.4mm² Earth Terminal Capacity				
Plate Finish Hartland CFX Satin Brass Insert Colour White EAN13 Barcode 5017504250041 Commodity Code 858363010 Luckins TSI 388237689 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Maximum Load 2 Amp IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 4x 1.5mm² Earth Terminal Capacity 3	Primary Range	Hartland CFX		
Insert Colour White EAN13 Barcode 5017504250041 Commodity Code 85383010 Luckins TSI 388237689 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x/mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 4 <td< td=""><td>Insert Type</td><td colspan="2">1 gang 2A Unswitched Socket</td></td<>	Insert Type	1 gang 2A Unswitched Socket		
EAN13 Barcode 5017504250041 Commodity Code 85363010 Luckins TSI 388237689 ETIM Class E C000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 4x 1.5mm² Earth Terminal Capacity 4 1x 4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x 4mm² Earth Terminal Capacity 4 1x 4mm² Earth Terminal Capacity 4<	Plate Finish			
Commodify Code 85363010 Luckin TSI 388237689 ETIM Class EC000125 Dimensions (Nominal) Single: Helght = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 4 1x4mm² Five type of type of type of	Insert Colour	White		
Luckins TSI 388237689 ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Kining Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Mininum Wall Box Depth 35mm Switched Poles None Current Rating 2 Armp Voltage 200/250V AC Maximum Load 2 Armp Mains Frequency 50Hz IP Rating PXD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm2 Earth Terminal Capacity 3 2x2.5mm2 Earth Terminal Capacity 4 1x4mm² For 0x40°C 4x1.5mm² Bearth Terminal Capacity 4	EAN13 Barcode	5017504250041		
ETIM Class EC000125 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 2207,250V AC Maximum Load 2 Amp Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x 4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x 4mm² Froduct Class 1 Must be earthed Ambient Operating Temperature -5* to +40°C Recommended Location Internal Use Only Max	Commodity Code	85363010		
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Maximum Load 2 Fixing IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 5 5 t 5 t 40°C Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 5 5 t 5 t 40°C Earth Terminal Capacity 6 5 t 5 t 40°C	Luckins TSI	388237689		
Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x4mm² Froduct Class 1 Must be earthed Ambien Operating Temperature 5* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	ETIM Class	EC000125		
Minimum Wall Box Depth 35mm Switched Poles None Current Rating 2 Amp Voltage 200/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm2 Earth Terminal Capacity 4 1x4mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm		
Switched Poles None Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 3 2x 2.5mm² Earth Terminal Capacity 4 1x 4mm² Produc Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Current Rating 2 Amp Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval 8S 546	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x 1.5mm2 Earth Terminal Capacity 3 2x 2.5mm2 Earth Terminal Capacity 4 1x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Switched Poles	None		
Maximum Load 2 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4x 1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x 4mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval 8S 546	Current Rating	2 Amp		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Voltage	220/250V AC		
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Maximum Load	2 Amp		
Contact Gap Minimum Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 2 4 x 1.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 3 2 x 2.5mm² Earth Terminal Capacity 4 1 x 4mm² Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 546	Mains Frequency	50Hz		
Terminal Capacity 1 5 x1mm² Terminal Capacity 2 4x1.5mm² Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	IP Rating	IP2XD		
Terminal Capacity 2 4x1.5mm² Terminal Capacity 4 1x4mm² Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2x 2.5mm2 Earth Terminal Capacity 3 2x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Contact Gap Minimum	None		
Terminal Capacity 3 2x2.5mm² Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude Standard/Approval 2x2.5mm² 2x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Austropy C Internal Use Only BS 546	Terminal Capacity 1	5 x1mm²		
Terminal Capacity 41x4mm²Earth Terminal Capacity 15x1mm²Earth Terminal Capacity 24 x 1.5mm²Earth Terminal Capacity 32 x 2.5mm²Earth Terminal Capacity 41 x 4mm²Product Class 1Must be earthedAmbient Operating Temperature-5° to +40°CRecommended LocationInternal Use OnlyMaximum Installation Altitude2000mStandard/ApprovalBS 546	Terminal Capacity 2	4x1.5mm²		
Earth Terminal Capacity 1 5x1mm² Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Terminal Capacity 3	2x2.5mm²		
Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Terminal Capacity 4	1x4mm²		
Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 2	4 x 1.5mm2		
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 3	2 x 2.5mm2		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Earth Terminal Capacity 4	1 x 4mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 546	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS 546	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 546	Recommended Location	Internal Use Only		
	Maximum Installation Altitude	2000m		
Additional Notes Shuttered: Yes	Standard/Approval	BS 546		
	Additional Notes	Shuttered: Yes		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

72CUS2W

Hartland CFX Satin Brass 1 gang 2A Unswitched Socket White				
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445			
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:52 AM E&OE		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

SL

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









