

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

72CWR23SB-B

Hartland CFX Satin Brass Wide Rocker 3 gang 10AX Satin Brass/Black

Item Image Wiring Dimensions Primary Range Hartland CFX Wide Rocker - 3 gang 10AX 2 Way Rocker Insert Type Wide Rocker - 3 gang 10AX 2 Way Rocker Palar Finish Hartland CFX Salin Brass Neer Colour Salin BrasseBlock EAN13 Barcodo GOST 14-0060224 Commotify Code Boss2010 Lucken STSI 453346531 ETM Class ECO01500 Dimensions (Nominal) Single: Height = 60.0mm Width = 80.0mm Depth = 5.0mm Finish pit-loc Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Winnerm Wall Box Depth Zimm Minimum Wall Box Depth Zimm Minimum Wall Box Depth Zimm Joan Joan	natuand CFX	Satin Brass Wide Rocker 3 gang 10AX Sat	III DIASS/DIAUK	
Primary Range	Item Image	Wiring	Dimensions	
Primary Range		_	_	
Insert Type		×	×	
Insert Type				
Flate Finish				
Insert Colour				
EAN13 Barcode 5051164008024 Commodity Code 85363010 Luckins TSI 45340631 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Cap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x5mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x5mm² Earth Terminal Capacity 6 1x5mm² Earth Terminal Capacity 7 1x5mm²				
Commodity Code				
Luckins TSI 453340631 ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² For Octuct Class 1 Must be earthed Ambient Operating Temperature -6* to +40°C Recommended Location Internal Use Only Maximum Installation Altitude				
ETIM Class EC001590 Dimensions (Nominal) Single: Height = 86.0mm	-			
Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 6 1x6mm² Earth Terminal Capacity 7 1x6mm² Earth Terminal Capacity 8 1x6mm² Earth Terminal Capacity 9 1x6mm²				
Fixing Hole Centres				
Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Switched Poles Single Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x5mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Current Rating 10AX Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Voltage 220/250V AC Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Maximum Load 10 Amp inductive Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	-			
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x6mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Earth Terminal Capacity 4 5x4m² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 3 1x4mm² Multi-strand Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Mains Frequency	·		
Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Contact Gap Minimum			
Terminal Capacity 2 1x4mm² Multi-strand Terminal Capacity 3 1x6mm² Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Terminal Capacity 1			
Earth Terminal Capacity 1 6x1mm² Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked		1x4mm² Multi-strand		
Earth Terminal Capacity 2 4x1.5mm² Earth Terminal Capacity 3 2x2.5mm² Earth Terminal Capacity 4 1x4mm² Multi-strand Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Terminal Capacity 3	1x6mm²		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Ix4mm² Multi-strand Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes CE Marked	Earth Terminal Capacity 1	6x1mm²		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1x6mm² Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes 1x4mm² Multi-strand 1x6mm² Must be earthed -5° to +40°C Recommended Location Internal Use Only 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Earth Terminal Capacity 2	4x1.5mm²		
Earth Terminal Capacity 5 1x6mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Earth Terminal Capacity 3	2x2.5mm²		
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Earth Terminal Capacity 4	1x4mm² Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked	Earth Terminal Capacity 5	1x6mm²		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Standard/Approval BS EN 60669-1 Additional Notes CE Marked				
Additional Notes CE Marked				
Module Size Height = 67mm Width = 67mm Depth = 23mm				
	Module Size	Height = 67mm Width = 67mm Depth = 23mm		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

72CWR23SB-B

Hartland CFX Satin Brass Wide Rocker 3 gang 10AX Satin Brass/Black			
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:52 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









