Hamilton

making connections beautifully

	Wiring Accessories •	Smart Lighting Control • Wireless Audio	
<u>74C3XTMSS-B</u>			
Hartland CFX Satin Steel Effect 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Satin Steel/Black			
Item Image	Wiring	Dimensions	
	Multi- Way Wiring using Slave module(s)	HEIDICA SITM Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer	
Primary Range	Hartland CFX		
Insert Type	3 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer		
Plate Finish	Hartland CFX Satin Steel Effect		
Insert Colour	Satin Steel/Black		
EAN13 Barcode	5017504009649		
Commodity Code	85363010		
Luckins TSI	391559862		
ETIM Class	EC000025		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	250W Resistive 210VA Inductive		
Switched Poles	N/A		
Current Rating	1.1 Amps per gang		
Voltage	220/250V AC		
Maximum Load	250W Resistive per gang 210VA Inductive Min Load 25W/25VA		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Terminal Capacity 1	1V/A 2x1mm ²		
Terminal Capacity 2	2x1.5mm ²		
Earth Terminal Capacity 1	5x1mm ²		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product)		

SL

Hamilton

making connections beautifully

CERT. No. FM11238

Wiring Accessories • Smart Lighting Control • Wireless Audio

74C3XTMSS-B

Hartland CFX Satin Steel Effect 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Satin Steel/Black

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:52 AM E&OE
	ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble LUCKINS

SL