




## 74CK21B

### Hartland CFX Satin Steel Effect 1 gang 20AX 2 Way Key Switch Black

Item Image	Wiring	Dimensions
		
Primary Range	Hartland CFX	
Insert Type	1 gang 20AX 2 Way Key Switch	
Plate Finish	Hartland CFX Satin Steel Effect	
Insert Colour	Black	
EAN13 Barcode	5017504261696	
Commodity Code	85363030	
Luckins TSI	388238031	
ETIM Class	EC000029	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x1mm <sup>2</sup>	
Terminal Capacity 2	4x1.5mm <sup>2</sup>	
Terminal Capacity 3	2x2.5mm <sup>2</sup>	
Terminal Capacity 4	2x4mm <sup>2</sup> Multi-strand	
Terminal Capacity 5	1x6mm <sup>2</sup>	
Earth Terminal Capacity 1	6x1mm <sup>2</sup>	
Earth Terminal Capacity 2	5x1.5mm <sup>2</sup>	
Earth Terminal Capacity 3	3 x2.5mm <sup>2</sup>	
Earth Terminal Capacity 4	2x4mm <sup>2</sup> Multi-strand	
Earth Terminal Capacity 5	1x6mm <sup>2</sup>	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	

## 74CK21B

### Hartland CFX Satin Steel Effect 1 gang 20AX 2 Way Key Switch Black

Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 08:53 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble**  
**LUCKINS**



CERT. No. FM11238