



74CSS1SS-W

Hartland CFX Satin Steel Effect 1 gang 13A Double Pole Switched Socket Satin Steel/White

Item Image	Wiring	Dimensions
		
Primary Range	Hartland CFX	
Insert Type	1 gang 13A Double Pole Switched Socket	
Plate Finish	Hartland CFX Satin Steel Effect	
Insert Colour	Satin Steel/White	
EAN13 Barcode	5017504267018	
Commodity Code	85363010	
Luckins TSI	388238921	
ETIM Class	EC000125	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm	
Weight	162 GR	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	13 Amp	
Voltage	220/250V AC	
Maximum Load	13 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	4x2.5mm ²	
Terminal Capacity 2	3x4mm ²	
Terminal Capacity 3	2x6mm ² Multi-Strand	
Terminal Capacity 4	1x10mm ²	
Earth Terminal Capacity 1	4x2.5mm ²	
Earth Terminal Capacity 2	3x4mm ²	
Earth Terminal Capacity 3	2x6mm ² Multi-Strand	
Earth Terminal Capacity 4	1x10mm ²	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Dual Earth: Yes	

74CSS1SS-W

Hartland CFX Satin Steel Effect 1 gang 13A Double Pole Switched Socket Satin Steel/White

<p>Patents and Trademarks</p>	<p>CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 =3023445</p>	
<p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p>	<p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>	<p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p>
<p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>	<p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p>	<p>Correct as at 05 July 2022 08:53 AM E&OE</p>

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **Trimble LUCKINS™**



CERT. No. FM11238