



Wiring Accessories • Smart Lighting Control • Wireless Audio

## **74CWR31SS-B**

| Hartland CFX Satin Stainless Steel Effect Wide Rocker 1 gang 10AX Intermediate Satin Steel/Black |  |                  |  |
|--|--|------------------|--|
| Item Image   | Wiring   | Dimensions       |  |
| nom mage   | ······································               | 2 intertellation |  |
|  | ×  | ×                |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
|  |  |                  |  |
| Primary Range  | Hartland CFX   |                  |  |
| Insert Type  | Wide Rocker - 1 gang 10AX Intermediate Rocker        |                  |  |
| Plate Finish   | Hartland CFX Satin Steel Effect                      |                  |  |
| Insert Colour  | Satin Steel/Black                                    |                  |  |
| EAN13 Barcode  | 5051164009434  |                  |  |
| Commodity Code   | 85363010   |                  |  |
| Luckins TSI  | 453340831  |                  |  |
| ETIM Class   | EC001590   |                  |  |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm |                  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = CFX Clips          |                  |  |
| Minimum Wall Box Depth   | 25mm   |                  |  |
| Switched Poles   | Single   |                  |  |
| Current Rating   | 10AX   |                  |  |
| Voltage  | 220/250V AC  |                  |  |
| Maximum Load   | 10 Amp inductive                                     |                  |  |
| Mains Frequency  | 50Hz   |                  |  |
| IP Rating  | IP2XD  |                  |  |
| Contact Gap Minimum  | 3mm  |                  |  |
| Terminal Capacity 1  | 3x2.5mm²   |                  |  |
| Terminal Capacity 2  | 1x4mm² Multi-strand                                  |                  |  |
| Terminal Capacity 3  | 1x6mm²   |                  |  |
| Earth Terminal Capacity 1  | 6x1mm <sup>2</sup>                                   |                  |  |
| Earth Terminal Capacity 2  | 4x1.5mm²   |                  |  |
| Earth Terminal Capacity 3  | 2x2.5mm²   |                  |  |
| Earth Terminal Capacity 4  | 1x4mm² Multi-strand                                  |                  |  |
| Earth Terminal Capacity 5  | 1x6mm²   |                  |  |
| Product Class 1  | Must be earthed                                      |                  |  |
| Ambient Operating Temperature  | -5° to +40°C   |                  |  |
| Recommended Location   | Internal Use Only                                    |                  |  |
| Maximum Installation Altitude  | 2000m  |                  |  |
| Standard/Approval  | BS EN 60669-1  |                  |  |
| Additional Notes   | CE Marked  |                  |  |
| Module Size Height = 67mm Width = 67mm Depth = 22mm  |  |                  |  |
|  |  |                  |  |



making connections beautifully

## Wiring Accessories • Smart Lighting Control • Wireless Audio

## 74CWR31SS-B

| Hartland CFX Satin Stainless Steel Effect Wide Rocker 1 gang 10AX Intermediate Satin Steel/Black  |   |  |  |
|---|---|--|--|
| Patents and Trademarks  | CFX is a Registered Trade Mark No 2398667<br>Hartland CFX is a Registered Design under Reference Nos.<br>R21 = 3023446 SS2 =3023445 |  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.                               | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice. |  |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                      | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.                       | Correct as at 05 July 2022 08:53 AM<br>E&OE  |  |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









