

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

70CDTVFW

Hartland CEX Gloss White 1 gang Non-Isolated TV (Female) (DAB Compatible) White

| Item Image | Wiring | Dimensions |
|---|--|--|
| | EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable | Hamilton HARTLAND CFX DTVF Non-Isolated TV (female) |
| | | 50.0 50.0 50.0 50.0 50.0 50.0 50.0 50.0 |
| Primary Range | Hartland CFX | |
| Insert Type | 1 gang Non-Isolated TV (female) (DAB Compatible) | |
| Plate Finish | Hartland CFX Gloss White | |
| Insert Colour | White | |
| EAN13 Barcode | 5017504008611 | |
| Commodity Code | 85367000 | |
| Luckins TSI | 398264354 | |
| ETIM Class | EC000439 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 5.0mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | N/A | |
| Current Rating | n/a | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Earth Terminal Capacity 1 | 5x1mm² | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed (ref BS7671 415.2.1) | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 5733. BS EN 50083-2: 2012/A1:2015. BS EN 61169-2:2007 | |
| EuroFix Additional Notes | TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet | |
| Frequencies 1 | TV DC=5-2200 MHz | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 05 July 2022 08:48 AN E&OI |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











