

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

70CUS99W

Hartland CFX Gloss White 2 gang 13A Unswitched Socket White

Primary Range	Item Image	Wiring	Dimensions	
Insert Type		Earth	US99 Unswitched Socket	
Plate Finish Hartland CFX Gloss White Insert Colour White EAN13 Barcode 5017564008987 Commodity Code 85363010 Luckins TSI 398266501 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3x 4mm² Earth Terminal Capacity 3 2x 6mm² Multi-strand Earth Terminal Capacity 3 2x 6mm² Multi-strand	Primary Range	Hartland CFX		
Insert Colour	Insert Type	2 gang 13A Unswitched Socket		
EAN13 Barcode 5017504008987 Commodity Code 85363010 Luckins TSI 398266501 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum None Terminal Capacity 1 32.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x5mm² Multi-strand Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 3 1x 10mm² Earth Terminal Capacity 4 1x 10mm² Earth Terminal Capacity 5 1x 10mm² Earth Terminal Capacity 6 1x 10mm² Earth Terminal Capacity 7 1x 10mm² Earth Terminal Capacity 8 1x 10mm² Earth Terminal Capacity 9 1x 10mm² Earth Terminal Capacity 1 1x 10mm² Earth Terminal Capacity 1 1x 10mm² Earth Terminal Capacity 3 1x 10mm² Earth Terminal Capacity 4 1x 10mm² Earth Terminal Capacity 4 1x 10mm² Forduct Class 1 Must be earthed Ambient Operating Temperature 5° 10 +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval	Plate Finish	Hartland CFX Gloss White		
Commodify Code 85383010 Luckins TSI 388268501 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² </td <td>Insert Colour</td> <td colspan="3">White</td>	Insert Colour	White		
Luckins TSI 398266501 ETIM Class EC000125 Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 3 2x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm²<	EAN13 Barcode	5017504008987		
ETIM Class EC000125 Dimensions (Nominal) Double: Helight = 86.0mm Width = 145.0mm Depth = 5.0mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/2560V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1x 10mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature	Commodity Code	85363010		
Dimensions (Nominal) Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm	Luckins TSI	398266501		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	ETIM Class	EC000125		
Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1x 10mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm		
Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval 8S 1363-2	Minimum Wall Box Depth	35mm		
Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Switched Poles	None		
Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Current Rating	·		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Voltage			
IP Rating	Maximum Load	13 Amp		
Contact Gap Minimum None Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 3 2x 6mm2 Multi-strand Earth Terminal Capacity 3 1x 10mm² Earth Terminal Capacity 4 1x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-2	Mains Frequency			
Terminal Capacity 1 3x2.5mm² Terminal Capacity 2 3x4mm² Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 2x6mm² Multi-strand Terminal Capacity 4 1x10mm² Earth Terminal Capacity 1 2x5mm² Earth Terminal Capacity 2 3x 4mm2 Earth Terminal Capacity 2 2x 6mm² Multi-strand Earth Terminal Capacity 3 2x 6mm² Multi-strand Earth Terminal Capacity 4 1x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval BS 1363-2	Contact Gap Minimum	None		
Terminal Capacity 3 2x6mm² Multi-strand 1x10mm² Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 2 3 x 4mm² Earth Terminal Capacity 3 2 x 6mm² Multi-strand Earth Terminal Capacity 4 1 x 10mm² Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Terminal Capacity 1	3x2.5mm²		
Terminal Capacity 4 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 I x 10mm2 Product Class 1 Ambient Operating Temperature Ambient Operating Temperature For to +40°C Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Internal Use Only BS 1363-2	Terminal Capacity 2	3x4mm²		
Earth Terminal Capacity 1 3x2.5mm² Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Terminal Capacity 3	2x6mm² Multi-strand		
Earth Terminal Capacity 2 3 x 4mm2 Earth Terminal Capacity 3 2 x 6mm2 Multi-strand Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Terminal Capacity 4	1x10mm²		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval 2 x 6mm2 Multi-strand 1 x 10mm2 Must be earthed -5° to +40°C Recommended Location Internal Use Only BS 1363-2	Earth Terminal Capacity 1	3x2.5mm²		
Earth Terminal Capacity 4 1 x 10mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 2	3 x 4mm2		
Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Earth Terminal Capacity 4	1 x 10mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 1363-2	Product Class 1	Must be earthed		
Maximum Installation Altitude2000mStandard/ApprovalBS 1363-2	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS 1363-2	Recommended Location			
	Maximum Installation Altitude	2000m		
Additional Notes Shuttered: Yes	Standard/Approval	BS 1363-2		
	Additional Notes	Shuttered: Yes		



making connections beautifully

Willing Accessories	Smart Lighting Control .	VVII eless Audic

70CUS99W

Hartland CFX Gloss White 2 gang 13A Unswitched Socket White					
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445				
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.			
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 05 July 2022 08:49 AM F&OF			

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









