

making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7WPCDSAT+B

Hartland CFX Primed White Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible) Black

Item Image	Wiring	Dimensions	
	Cable Clarry Screw Terminal Conductor Termin	HARTLAND CFX DSAT+ Non-Isolated TVFWWSatellite1/Satellite2 Quadplexer 2in/4out + TVF + TCS	
Primary Range	Hartland CFX		
Insert Type	Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible)		
Plate Finish	Hartland CFX Primed White		
Insert Colour	Black		
EAN13 Barcode	5017504015268		
Commodity Code	85367000		
Luckins TSI	398332231		
ETIM Class	EC000439		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 5.0mm		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	N/A		
Current Rating	n/a		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Earth Terminal Capacity 1	5x1mm²		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed (ref BS7671 415.2.1)		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS 5733. BS EN 50581:2012. BS EN 60728-4:2008. BS EN 50083-2: 2012/A1:2015. BS EN 61169-2:2007		
EuroFix Additional Notes	Quadplexer for use with combined TV FM and Satellite Signals (DAB compatible) plus Telephone Slave and Female TV Socket		
Frequencies 1	TV=5-68 MHz 125-860 MHz		
Frequencies 2	FM=88-108 MHz		
Frequencies 3	SAT DC=950-2200 MHz		
Frequencies 4	TV DC=5-2200 MHz		



making connections beautifully

Wiring Accessories • Smart Lighting Control • Wireless Audio

7WPCDSAT+B

Hartland CFX Primed White Non-Isolated TV+FM+SAT1+SAT2 Quadplexer 2in/4out +TVF+TCS (DAB Compatible) Black

(
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Hartland CFX is a Registered Design under Reference Nos. R21 = 3023446 SS2 = 3023445		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 05 July 2022 09:02 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









